



Rated #1

This model was rated as Number One by a leading consumer magazine.

30" Electric Drop-In Cooktop Specifications

- Product Weight – 35 Lbs.
- Single phase 3- or 4-wire cable, 120/240 or 120/208 Volt, 60 Hertz, fused on both sides of line with ground.
- Connected Load (kW Rating) – 240/208 Volts = 8.76/6.58 kW
- Amps @ 240/208 Volts = 36.2/31.4 Amps
- Always consult local and/or national electric codes.
- Allow 2" space below armoured cable opening to clear electrical cable and allow space for installation of junction box on wall at back of cooktop.
- Overhead cabinetry should not exceed a 13" maximum depth.
- Allow 30" minimum clearance between top of cooktop and bottom of unprotected wood or metal overhead cabinetry.
- The absolute minimum horizontal distance between overhead cabinets installed to either side of the appliance must be no less than the maximum width of the appliance.
- Allow 24" minimum clearance when bottom of wood or metal overhead cabinet is protected by not less than 1/8" flame-retardant millboard covered with not less than No. 28 MGS sheet steel, 0.015" stainless steel, 0.024" aluminum or 0.020" copper.
- Allow 2" minimum clearance between rear edge of cutout and nearest combustible surface above countertop.
- Allow 7-1/2" minimum clearance from edge of cooktop to nearest combustible wall on either side of unit.
- It is recommended that drawers not be used beneath cooktop.
- To reduce risk of fire when using overhead cabinetry, install range hood that projects horizontally a recommended minimum of 7" beyond bottom of cabinets.

NOTE: Refer to Product Installation Guide for detailed instructions on the web at electroluxusa.com.

Versatile, Flexible

Five Element Configuration

Concentric rings in double and triple elements are clearly marked on the surface. Expandable elements allow you to cook with a variety of pan sizes at up to 2700 watts.

Easy to Clean

One look says it all. This superior ceramic smoothtop glass surface is durable, smooth and easy to clean. The glass ceramic surface easily buffs to a glossy shine. Imagine the beauty this sleek, glistening cooktop will bring to your kitchen.

Easy Set™ Electronic Controls

Whether bringing water to a quick boil in a large pot or simmering your favorite hollandaise sauce, these convenient elements offer all the flexibility you require.

30" ELECTRIC DROP-IN COOKTOP

Configuration	5 Electric Elements
---------------	---------------------

FEATURES

Black Ceramic Smoothtop Glass Surface	Yes
Large Professional Knobs with Bezel	5
5" to 7" to 9" Expandable Element – 1000 W/1800 W/2700 W	1
5" to 7" Dual Element – 750 W/1800 W	2
6" Element – 1200 W	2
Hot Surface Indicator Lights (H. S. in displays)	5 Positions
Spill Control Cooktop	Yes

SPECIFICATIONS

Cutout Dimensions –	
Height	6" min.
Width	29-5/8" min. 30" max.
Depth	20-1/4" min. 20-1/2" max.
Power Supply Location	Middle Rear
Connected Load Rating - 240/208 Volts	8.76/6.58 kW
Electrical – Single phase 3- or 4- wire cable, 120/240 V or 120/208 V, 60 Hz, fused on both sides of line with ground.	Required
Armored Electrical Cable	Included
Product Weight	35 Lbs.
Shipping Weight	40 Lbs.
UPC (0-57112-)	08926-3

NOTE: Always consult local and/or national electric codes. Refer to Product Installation Guide for detailed installation instructions on the web at electroluxusa.com.

