

LCD Televisions – Specifications

Features/Models		TC-26LX70	TC-32LX70	TC-32LX700
<b>Video</b>				
Screen size diagonal		26"	32"	32"
Aspect ratio		16:9	16:9	16:9
Panel		IPS	IPS	IPS (ALPHA)
Number of pixels		1,049,088 (1,366 x 768)	1,049,088 (1,366 x 768)	1,049,088 (1,366 x 768)
Brightness (Panel luminance)		500 cd/m <sup>2</sup>	500 cd/m <sup>2</sup>	500 cd/m <sup>2</sup>
Dynamic contrast ratio		7000:1	7000:1	8500:1
Response time		8 msec	8 msec	6 msec
Viewing angle		178°	178°	178°
Motion adaptive 3D Y/C digital comb filter		•	•	•
HDTV display capability (1080p <sup>1</sup> , 1080i, 720p) <sup>2</sup>		•	•	•
EDTV display capability (480p) <sup>2</sup>		•	•	•
Aspect control (SDTV/EDTV)		Full, Just, 4:3, Zoom	Full, Just, 4:3, Zoom	Full, Just, 4:3, Zoom
Aspect control (HDTV)		Full, H-Fill, Just, 4:3, Zoom	Full, H-Fill, Just, 4:3, Zoom	Full, H-Fill, Just, 4:3, Zoom
Progressive scan		•	•	•
Motion picture pro™		--	--	•
Intelligent scene controller™		•	•	•
3D colour management		•	•	•
Sub-pixel controller		•	•	•
Digital cinema reality (3:2 pull down)		480i only	480i only	480i only
<b>Audio</b>				
Speakers		Full-range x 2 (L, R)	Full-range x 2 (L, R)	Tweeter x 2, Woofer x 2 (L, R)
Number of speakers		2	2	4
Audio output		20 W (10% THD) <sup>4</sup>	20 W (10% THD) <sup>4</sup>	20 W (10% THD) <sup>3</sup>
BBE® ViVA HD3D Sound		--	--	•
Surround Sound		•	•	•
AI Sound		•	•	•
Audio leveler		•	•	•
Speakers on/off		•	•	•
<b>Jacks</b>				
Integrated ATSC/NTSC tuner		•	•	•
SD memory card slot		--	--	• (SDHC compatible)
HDMI input		2	2	2
Composite video input (rear/side)		2/1	2/1	2/1
S-Video input		2	2	2
Component video input (Y, Pb, Pr)		1	1	1
Composite video output		1	1	1
Analogue audio output		1	1	1
Digital audio output		1	1	1
Headphone jack		1	1	1
<b>Convenience</b>				
EZsync™		•	•	•
Trilingual menu (English/Spanish/French)		•	•	•
Multi-brand system remote		N2QAYB000102	N2QAYB000102	N2QAYB000100
V-Chip program lock out		•	•	•
Built-in closed caption decoder		•	•	•
On/Off sleep timers (5 programmable)		•	•	•
Video picture memory		•	•	•
Video input labelling		•	•	•
<b>General</b>				
Power supply		AC 120 V / 60 Hz	AC 120 V / 60 Hz	AC 120 V / 60 Hz
Power consumption	Average use	116 W	132 W	138 W
	Stand-by condition	0.1 W	0.1 W	0.1 W
Energy Star® qualified		•	•	•
Receiving system		ATSC / NTSC	ATSC / NTSC	ATSC / NTSC
Dimensions with stand (W x H x D)	mm	657 x 515 x 239	791 x 592 x 239	836 x 592 x 248
	inch	25.9 x 20.3 x 9.4	31.1 x 23.3 x 9.4	32.9 x 23.3 x 9.8
Dimensions without stand (W x H x D)	mm	657 x 468 x 117	791 x 545 x 117	836 x 540 x 107
	inch	25.9 x 18.4 x 4.6	31.1 x 21.5 x 4.6	32.9 x 21.3 x 4.2
Weight		14 kg / 30.9 lb	16.5 kg / 36.4 lb	18 kg / 39.7 lb
Swivel angle		NA	NA	± 15°
VESA compatible		200 x 100 mm	200 x 100 mm	200 x 100 mm
Gross weight		18 kg / 39.7 lb	21 kg / 46.3 lb	22 kg / 48.5 lb

<sup>1</sup> Available through HDMI only.

<sup>2</sup> All signals will be converted to match the panel's native resolution.

<sup>3</sup> 2-Way speaker system (8 ohms, 350Hz-17kHz / 80Hz-350Hz)

<sup>4</sup> Full range speaker system (8 ohms, 80Hz-17kHz)