

Maytag® Neptune® Drying Center™ Features And Specifications

Available in electric or gas. Electric model requires a 240-volt, 30-amp hookup; gas model requires a 120-volt, 20-amp hookup. Dimensions for both models are 33 1/2" (85.1 cm) W x 74" (188.0 cm) H x 29" (73.7 cm) D.

Model	MCE/G8000
Upper Drying Cabinet Features	
Capacity — cu. ft.	17.3
Controls	LED
BreezeCare™ Drying System	•
Dry Clothes Cycle	•
Refresh Cycle	•
Low Temperature	•
Extra-Low Temperature	•
Wrinkle Release Option	•
Remove Odor Option	•
Add Fragrance Option	•
Time Remaining Indicator	•
Cycle Status Indicator	•
Adjustable Time	•
WrinkleRelease™ Rod	•
Removable Mesh Shelves	5
ShapeSaver™ Hangers	•
Accessory Hooks	4
Dryer Sheet Caddy™	•
Water Bottle	•
Interior Cabinet Light	•
Shelf Storage Hanger	•
End-Of-Cycle Chime	Adjustable
Tumble Dryer Features	
Capacity — cu. ft.	7.0
Controls	LED
GentleBreeze™ Drying System	•
IntelliDry® Dryness Control	•
Temperature Settings	4
Sensor Dry Cycle	•
Time Dry Cycle	•
Air Fluff Cycle	•
Wrinkle Release Cycle	•
Wrinkle Prevent Option	•
Damp Dry Signal	•
Time Remaining Indicator	•
Cycle Status Indicator	•
End-Of-Cycle Chime	Adjustable
Reversible Door	•
High-Capacity Blower	•
Drum Light	•
DuraCushion™ Dryer Drum	•
Electric Dryer Venting Directions	2
Gas Dryer Venting Directions	2
Sound-Silencing System	EQ™ Plus

Dimensions for electric and gas models.

Overall Dimensions	in. (cm)
Width	33 1/2 (85.1)
Height	74 (188.0)
Depth	29 (73.7)

DRYER CONTROLS: Electronic LED.

UPPER MOTOR: 65W, 120-volt, 60 Hz, single-phase, thermoprotected against overload, automatic reset.

LOWER MOTOR: 245W, 120-volt, 60 Hz, single-phase, thermoprotected against overload, automatic reset.

UPPER CABINET AIRFLOW: 80 cubic feet (2.3 cu. m) per minute.

TUMBLE DRYER AIRFLOW: 175 cubic feet (6.2 cu. m) per minute.

EXHAUST: Use a minimum of 4" (10.2 cm) diameter rigid aluminum or galvanized-steel duct. Never use plastic, nonmetal or combustible duct.

UPPER HEATING ELEMENT (Both Models): Tubular heater, 1,200W, 10A.

TUMBLE DRYER HEATING ELEMENT (MCE Model): Open coil; 4,800W, 21A when using tumbler only; 3,400W, 14A when using tumbler and upper cabinet.

SINGLE-PORT BURNER (MCG Model): Automatic electric burner with automatic ignition.

AUTOMATIC PRESSURE REGULATOR (MCG Model): Self-adjusting valve automatically compensates for variation in gas pressure.

ELECTRICAL RATING (MCE Model): 240-volt, AC, 60 Hz, draws approximately 5,550W overall.

ELECTRICAL RATING (MCG Model): 120-volt, AC, 60 Hz, draws approximately 1,750W overall.

GAS RATING (MCG Model): 22,000 BTU/hr. for tumble dryer.

FUSE REQUIREMENTS:

MCE model: 30A.

MCG model: 20A.

LEVELING LEGS: Adjustable to level unit for proper installation.

WEIGHT (Crated/Uncrated): 273 lbs. (124 kg)/241 lbs. (109 kg).

Available in White or Bisque.