

DA 2588

Insert ventilation hood
with energy-efficient LED lighting and backlit controls for easy use.



- Customized kitchen design - fully integrated in 31 5/8 (802)Inch width
- Unique user convenience – Con@ctivity
- Efficient filtration- 10-ply stainless steel grease filters
- Safe and easy to clean - Miele CleanCover

EAN: 4002516024705 / material number: 10876770

Construction type	
Insert ventilation hood	•
Design	
Color	Stainless steel
RAL color possible as special order	•
Customization possible on request	•
Operating modes	
Recirculated mode	Convertible
OdorFree charcoal filter (order separately)	DKF15-900
Control panel	
Electronic controls	•
Light-touch controls	•
Power levels (number excl. Intensive)	3
Intensive setting	•
Programmable 'Intensive' switch-off	•
Delayed shutdown for 5 or 15 minutes	•
Programmable grease filter saturation indicator	•
Programmable charcoal filter saturation indicator	•
Cleaning convenience	
CleanCover	•
Networking of domestic appliances	
Miele@home	•
WiFiConn@ct	•
Automatic function Con@ctivity 2.0 (Zigbee)	•
Filter system	
Number of dishwasher-safe stainless-steel grease filters	2
Lighting	
LED ClearView lighting	•
Light intensity in Lx	300
Color temperature in K	3,000
Blower	
Dual-action blower	•
AC motor	•
Air throughput with max. duct diameter in vented mode (not for external version)	
Air throughput	Values upon request
Safety	
Safety shut-off	•
Technical data	
Canopy width in in.(mm)	31 5/8 (802)
Height of hood canopy in in.(mm)	2 (50)
Depth of hood canopy in in.(mm)	15 7/8 (402)
Minimum distance above electric cooktops in in.(mm)	24 1/8 (610)
Minimum height above gas cooktop (max. 12.6 kW total power, burner 4.5 kW) in mm	26 (660)
Net weight in lbs. (kg)	27 (12.1)
Length of electrical wire in ft (m)	2 (0.9)
Standard plug fitted	•
Total connected load in kW	0.36
Voltage in V	120
Fuse rating in A	15
Number of phases	1

More information at www.MieleUSA.com

For further information please see next page...

DA 2588

Insert ventilation hood
with energy-efficient LED lighting and backlit controls for easy use.



Installation notes	
Vent connection at top	•
Diameter of vent connection in in.(mm)	6 (150)
Standard accessories	
Non-return flap	•
Reducer from 150 to 125 mm Ø	•
Wireless stick Con@ctivity 2.0 for KM	XKS 3000 Z