



New COOLSHOT 50i



DUAL LOCKED ON QUAKE

Visual and gentle vibration cue that you are ranging the flag and not something behind it.



OLED DISPLAY

High visibility red display provides ideal contrast on distant targets.



MULTILAYER COATING

Multilayer coating is applied to one or more lens and prism surfaces.



ID TECHNOLOGY

Delivers the one number you need for your best shot to account for incline or decline shooting angles.



INTEGRATED MAGNET

Built in mounting magnet safely connects to metal surfaces for convenient storage.



LONG EYE RELIEF

Provides 15mm or more of eye relief. Perfect for eyeglass wearers.



RAINPROOF

PX4 rated — allows you to continue use even in the rain.

DUAL LOCKED ON QUAKE technology.

Targeting the pin? DUAL LOCKED ON QUAKE confirms you've hit the flag and not something in the background. It provides a visual cue and a gentle vibration to signify that you're measuring the pin, not a tree or other object 20 yards behind it.



Mount up.

With an innovative built-in mounting magnet, the COOLSHOT 50i safely connects to metal surfaces†— your cart, or even your bag carrier. Grab it. Use it. Stick it back on.



†When attaching to magnetic metals using the rangefinder's internal magnet, make sure that the rangefinder is securely set in place. It may fall due to vibration or impact.

Users of medical devices such as cardiac pacemakers should not use this product and its accessories. Magnets built into the product and accessories can cause medical device malfunctions. Also, keep credit cards and electronic media away from this product and its accessories. Recorded data may get corrupted.

Competition approved.

When slope-compensation is not allowed, the Actual Distance Indicator (ADI) LED tells your competition you're not using the ID Technology mode.



All Nikon products include Nikon Inc. limited warranty. Nikon Authorized Dealers and Resellers set their own selling prices, which may vary.

©2021 All Nikon Trademarks are the property of Nikon Corporation. Features and specifications are subject to change without notice.



Grab and go.

The first Nikon golf rangefinder with a built-in mounting magnet— attach it wherever it's convenient! A lightweight rainproof exterior protects Nikon's brilliant optics with anti-glare coating and a vibrant OLED screen. Fast, accurate measurements made easy with DUAL LOCKED ON QUAKE technology, slope adjustment, continuous measurement mode and more.

SPECIFICATIONS	COOLSHOT 50i
PRODUCT NUMBER	16760
MAG. X OBJ. DIAMETER	6 x 22
MEASUREMENT RANGE* (YDS) MAX RANGE (GUIDE FOR MEASUREMENT DISTANCE TO FLAGSTICK)* (YDS)	6-1,200 1,200/400 TO FLAGSTICK
ACCURACY** (ACTUAL DISTANCE IN YDS)	±1 M/YD. (SHORTER THAN 100 M/YD.) ±2 M/YD. (100 M/YD. AND OVER, SHORTER THAN 1,000 M/YD.) ±0.5% M/YD. (1,000 M/YD. AND OVER)
VIEWFINDER DISPLAY	m/YD
MAGNIFICATION	6x
ANGULAR FIELD OF VIEW (REAL)	6°
FOV @ 100 YDS. (FT.)	31.4
EYE RELIEF (MM)	17
DIOPTER ADJUSTMENT	±3 m-1
POWER SOURCE	1 CR2 lithium
SIZE (LXHXW) INCHES	3.9 x 3.0 x 1.5
WEIGHT (W/O BATTERIES) (OZ.)	6.2
OBJECTIVE DIAMETER (MM)	22
EXIT PUPIL (MM)	3.7
LASER CLASSIFICATION	IEC60825-1: CLASS 1M/LASER PRODUCT FDA/21 CFR PART 1040.10: CLASS 1 LASER PRODUCT
ELECTROMAGNETIC COMPATIBILITY	FCC PART 15 SUB PART B CLASS B, EU: EMC DIRECTIVE, ICES-3
ENVIRONMENT	ROHS, WEEE

*Under Nikon's measurement conditions and reference values.

**Under Nikon's measurement conditions.

The specifications of the product may not be achieved depending on the target object's shape, surface texture and nature, and/or weather conditions.

The technology behind the Laser Rangefinder with inclinometer originated from technology incorporated in Nikon's Total Station DTM-1 surveying instrument. The Total Station DTM-1, first sold in 1985, was the first highly advanced electronic model of those surveying instruments that incorporated a distance and angle measuring capability developed by Nikon Corporation.

Technical Information: 1-800-NIKON US
Service & Repair: www.nikonusa.com/service