



24" SIGNATURE SERIES
Freezer



eco friendly
R600a Refrigerant



JOB	
AREA	
ITEM NO.	
MODEL NO.	



Solid Door Model

MODELS	DESCRIPTION
HP24FS-4-1L/R	Indoor Signature Series Freezer Solid Stainless Steel Door
HP24FS-4-2L/R	Indoor Signature Series Freezer Solid Panel Ready Door
HP24FO-4-1L/R	Outdoor Signature Series Freezer Solid Stainless Steel Door
HP24FO-4-2L/R	Outdoor Signature Series Freezer Solid Panel Ready Door

KEY PRODUCT FEATURES AND BENEFITS

- 1000 BTU/hr capacity delivers industry's most energy efficient cool down; indoors or outdoors
- Up to 70% faster cooling speeds than leading competitor
- Variable speed compressor minimizes sound; up to 30% quieter than competitors
- Commercial-grade all stainless steel interior and exterior provides superior durability and easy cleaning
- Perlick Anti-Condensation System™ eliminates condensation from forming on the cabinet (outdoor models only)

Quick Features:

- Full extension shelving provides faster and safer product access with no reaching in the back of the cabinet; shelves fully extend on vibration dampened stainless steel ball bearing glides
- Industry's best full 6 year warranty for owner ease of mind
- Available with stainless steel or panel ready doors to match your design style
- Audible door alarm warns user if door is held open
- White LED task lighting
- R600a Natural Refrigerant offers maximum energy efficiency with zero ozone depletion potential
- Available storage racks for martini glasses and beer mugs allow you to store glasses with an assortment of liquors just like your favorite cocktail bar!



24" SIGNATURE SERIES
Freezer

MODEL NUMBERS		HP24FS	HP24FO
MODEL DESCRIPTION		24" Indoor Freezer	24" Outdoor Freezer
ATTRIBUTES			
Perlick Anti-Condensation System		NO	YES
OVERALL DIMENSIONS	Width - in. (mm)	23-7/8" (606 mm.)	23-7/8" (606 mm.)
	Depth - in. (mm)	24" (610 mm.)	24" (610 mm.)
	Height - in. (mm)	34-1/4" (870 mm.)	34-1/4" (870 mm.)
OPENING DIMENSIONS	Width - in. (mm)	24" (610 mm.)	24" (610 mm.)
	Depth - in. (mm)	24-7/8" (632 mm.)	24-7/8" (632 mm.)
	Height - in. (mm)	34-1/2" (876 mm.)	34-1/2" (876 mm.)
INTERNAL VOLUME Net. Cu. Ft.		5.2 cu. ft.	5.2 cu. ft.
SHIPPING WEIGHT Lbs. (kg.)		144 lbs (100.7 kg.)	144 lbs (100.7 kg.)
ELECTRICAL SPECIFICATIONS	Electrical Supply	115 VAC/60 Hz/1 Ph	115 VAC/60 Hz/1 Ph
	Running Load Amps	2.2 amps	2.2 amps
	Electrical Connection	Cord connected	Cord connected
	Cord Plug Type	NEMA 3 Prong 5-15P	NEMA 3 Prong 5-15P
	Cord Length	6'	6'
	Defrost Initiation	Hot Gas	Hot Gas
	Defrost Type	Off cycle	Off cycle
	Thermostat	Digital	Digital
REFRIGERATION SPECIFICATIONS	Refrigerant	R600a (57g)	R600a (57g)
	Expansion Device	Capillary Tube	Capillary Tube
	Temperature Settings F°(C°)	-10° (-23.3°) - 10° (-12.2°) Factory Set Point 36° (2.2°)	-10° (-23.3°) - 10° (-12.2°) Factory Set Point 36° (2.2°)
	Heat Rejection (at 75°F)	700 BTU/hr	700 BTU/hr
	Pull Down Capacity	1000 BTU/hr	1000 BTU/hr
	Front Vented	Yes	Yes
PLUMBING		None Required	None Required

Installation Notes: To achieve 24" install depth, place electrical connection adjacent to the installation cavity.

ACCESSORIES

MODEL NOS.	DESCRIPTION
(L)	Factory Installed Lock
67991-L/R	Stacking Kit for HP24/HC24/HA24 models
66736	Caster Kit for HP24/HC24/HA24 models
RS-24-24M	Martini Rack

Perlick accessories are available for purchase through an authorized Perlick dealer. For a full list of accessories and to find a dealer near you, visit perlick.com.



24" SIGNATURE SERIES

Freezer

CUSTOMER MODEL NUMBER	REGULATORY MODEL NUMBER	Hinge Side	Lock
HP24FS-4-1L	HP24FS4A-00-SLF0R	Left	No
HP24FS-4-1R	HP24FS4A-00-SRF0R	Right	No
HP24FS-4-2L	HP24FS4A-00-PL00R	Left	No
HP24FS-4-2R	HP24FS4A-00-PR00R	Right	No
HP24FS-4-1LL	HP24FS4A-00-SLFLR	Left	Yes
HP24FS-4-1RL	HP24FS4A-00-SRFLR	Right	Yes
HP24FS-4-2LL	HP24FS4A-00-PL0LR	Left	Yes
HP24FS-4-2RL	HP24FS4A-00-PR0LR	Right	Yes
HP24FO-4-1L	HP24FO4A-00-SLF0R	Left	No
HP24FO-4-1R	HP24FO4A-00-SRF0R	Right	No
HP24FO-4-2L	HP24FO4A-00-PL00R	Left	No
HP24FO-4-2R	HP24FO4A-00-PR00R	Right	No
HP24FO-4-1LL	HP24FO4A-00-SLFLR	Left	Yes
HP24FO-4-1RL	HP24FO4A-00-SRFLR	Right	Yes
HP24FO-4-2LL	HP24FO4A-00-PL0LR	Left	Yes
HP24FO-4-2RL	HP24FO4A-00-PR0LR	Right	Yes

