

# GAGGENAU



## AI 230 700

Stainless steel  
Width 40" (100 cm)  
Air extraction / Air recirculation  
Standard duct cover included

## Installation accessories

### AD 200 326

Stainless steel duct cover extension,  
Length: 3' 7 5/16" (1,100 mm).

### AD 223 346

Mounting kit extension.  
Length: 1' 7 1/16" (500 mm). Must  
be ordered in conjunction with the  
AD200326.

### AD 220 396

Stainless steel ceiling collar,  
covers screws on duct cover and  
uneven gaps of ceilings that are not  
completely flat.

## Optional accessories

### AA 200 816

Air recirculation module with activated  
charcoal filter installed on the inside  
of the duct cover.

### AA 200 110

Activated charcoal filter for AA200816  
air recirculation module.

### AD 223 356

Adapter for roof inclination left/right

### AD 223 366

Adapter for roof inclination front/back

## Good to know:

the hood has to be larger than the  
cooktop(s) or it has to be as large as the  
cooktop(s). Please check the require-  
ments in chapter ventilation.

## 200 series island hood

AI 230

- Classic Gaggenau design
- Highly efficient extraction of cooking vapors
- Low-noise blower
- Patented filter technology with high level of grease absorption
- Rim extraction filter with flat and easy-to-clean stainless steel surface
- Dimmable LED light for optimum illumination of the entire cooktop
- Air extraction or recirculation system
- Air recirculation module with activated charcoal filters: quiet and highly efficient recirculation solution with odor reduction as in air extraction mode, and long replacement intervals

## Output

Unobstructed air flow:  
490 CFM with  $\varnothing$  6".  
Sound pressure level: 61 dBA.  
Odor reduction recirculation 95%.

## Features


Three electronically controlled power levels and an intensive mode.  
Grease filter saturation indicator.  
Patented rim extraction filter, dishwasher-safe.  
Warm white LED light (3,600 K), continuously dimmable.  
Airflow-optimized interior for efficient air circulation.  
Easy mounting system for simple installation and alignment.  
A one-way flap comes included with the hood.

## Planning notes


The hood includes a two-part duct cover with dimensions from 2' 1 3/4" (654 mm) to 2' 8 13/16" (834 mm). Individual planning solutions can be accommodated using the optional duct cover accessory AD200326 or by shortening the lower edge of the telescopic duct cover.  
Minimum clearance above gas or induction cooktops is 30".  
The air recirculation module with activated charcoal filter can be installed on the inside of the duct cover.

## Rating


Total rating: 430 W.  
Total Amps: 3 A.  
120 V / 60 Hz  
Connecting cable 51 3/16" with plug.



\* Suitable for ceiling heights of 7.7 ft. (2.34 m) to 8.3 ft. (2.52 m);  
Specifications refer to a distance from floor to lower duct cover edge of 5.2 ft. (1.60 m).



\* Suitable for ceiling heights of 8 ft. (2.42 m) to 8.7 ft. (2.64 m);  
Specifications refer to a distance from floor to lower duct cover edge of 5.2 ft. (1.60 m).



\* Suitable for ceiling heights of 9.4 ft. (2.86 m) to 10.4 ft. (3.16 m);  
Specifications refer to a distance from floor and lower duct cover edge of 5.2 ft. (1.60 m).

Numbers indicated  
inside parenthesis ( ) = mm

www.gaggenau.com/us  
Revised: June 2021