


30" Induction Cooktop with Home Connect™, NIT8060UC, Black Frameless



Features and Benefits

Design

- 4 Induction Cooking Zones
- PreciseSelect® Premium - Direct Cooking Level Selection (17 Settings)
- Also Available with Stainless Steel Frame: NIT8060SUC

Efficiency

- SpeedBoost® - Adds Even More Power to Speed Up the Cooking Process
- ShortBoost - Ideal for Cooking With Oil, or Pans With Thin Walls or Non-Stick Coating
- PotSense - Automatically Recognizes Bottom of Pan on Cooking Element

Convenience

- With Home Connect®, the Bosch Cooktop and Matching Hood Operate Perfectly in Sync for an Easier Life
- Use the Kitchen Timer to Measure Cooking Time or as a Reminder
- Count Up Timer – Stopwatch Function That Enables Close Monitoring of the Progress of Each Dish
- AutoChef® Frying Sensor With 5 Automatic Programs
- Keep Warm Function - Low Setting for Keeping Food Warm at the Touch of a Button
- ReStart - Quickly Reinstates Previous Settings

Safety

- ChildLock - Prevents the Cooktop from Being Accidentally Switched On, Locks Temperature Settings if in Use
- Digital 2-Stage Residual Heat Indicator for Each Cooking Zone
- Wipe Protection - Quickly Pauses Settings to Clean as You Go





Notes: All height, width and depth dimensions are shown in inches. *Please refer to installation instructions prior to making cutout. BSH reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice. Consult the product's installation instructions for final dimensional data and other details. Applicable product warranty can be found in a accompanying product literature or you may contact your account manager for further details.

For more information on our entire line of products, go to boschappliances.com or call 1-800-944-2904.

Copyright ©2022 BSH Home Appliances Corporation. All rights reserved. Bosch is a registered trademark of Robert Bosch GmbH.

Litho Date: 02/2022

30" Induction Cooktop with Home Connect™, NIT8060UC, Black Frameless



Features

| | |
|---------------------------------------------------|-------|
| Knob Material | |
| Sealed Burners | No |
| Burners with booster | All |
| Type of grate | |
| Total BTU load | |
| LP Gas Connection Rating | |
| Power of heating element (kW in boost) | [2.2] |
| Dimension of 1st heating element (in) | 6" |
| Dimension of 2nd heating element (in) | |
| Power of 3rd heating element (kW in boost) | [3.6] |
| Dimension of 3rd heating element (in) | 9" |
| Power of 4th heating element (kW in boost) | |
| Dimension of 4th heating element (in) | |
| Power of 5th heating element (kW in boost) | [3.6] |
| Dimension of 5th heating element (in) | 11" |
| Power of 6th heating element (kW in boost) | |
| Dimension of 6th heating element (in) | |

Technical Specification

| | |
|--------------------------------------------------|-----------------------------|
| UPC code | 825225961499 |
| Variant color | Black |
| Energy source | Electric |
| Gas type | |
| Alternative gas type | |
| Watts | 6240 |
| Fuse protection | 30 |
| Volts | 208-240 |
| Frequency | 60 |
| Approval certificates | Dekra Mark C+US, FCC |
| Power Cord Length | 37" |
| Plug type | no plug |
| Required cutout size (HxWxD) (in) | 3 3/4" x 28 7/8" x 20" |
| Minimum distance from counter front (in) | 2 1/4" |
| Minimum distance from rear wall (in) | 2" |
| Overall appliance dimensions (HxWxD) (in) | 1/4"+3 3/4" x 31" x 21 1/4" |
| Product packaging dimensions (HxWxD) | 7 1/16" x 36 5/8" x 26 5/8" |
| Net weight | 40.000 |
| Gross weight | 48.000 |
| Total number of cooktop burners | 4 |

Notes: All height, width and depth dimensions are shown in inches. *Please refer to installation instructions prior to making cutout. BSH reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice. Consult the product's installation instructions for final dimensional data and other details. Applicable product warranty can be found in a accompanying product literature or you may contact your account manager for further details.