Canon EF Lens Specifications & Accessories Table

LENS	Apparent Focal length (mm)		Angle of View (35mm)***			Lens Construction (Groups/ Elements)	No. of Diaphragm Blades	Minimum Aperture (f)	Closest Focusing Distance		Maximum Magnification (x)	AF Actuator	Filter Diameter (mm)	Max Diameter x Length (in./mm)	Weight		Magnification w/Extension Tube EF 12 II	Magnification w/Extension Tube EF 25 II	Lens Hood	Hard Case	Soft Case	G. F Holder III (Hood III)*1	G.F Holder IV (Hood V) *1
	APS-H	APS-C	Horizontal	Vertical	Diagonal				(ft.)	(m)					(oz.)	(g)							
EF-S 10-22mm f/3.5-4.5 USM	N/A	16–35	97°10' – 54°30'	74°10' – 37°50'	107°30' – 63°30'	10/13	6	22	0.8	0.24	0.17	Ring USM	77	3.3/83.5 x 3.5/89.8	13.6	385	0.77–0.58	1.51–1.28	EW-83E	–	LP1319	NC	(0)
EF 16-35mm f/2.8L USM**	21–45	26–56	98° – 54°	74°10' – 38°	108°10' – 63°	10/14	7	22	0.9	0.28	0.22	Ring USM	77	3.3/83.5 x 4.1/103	1.3 lbs.	600	0.87–0.36	1.09–0.80	EW-83E	–	LP1319	NC	(0)
EF 17-40mm f/4L USM**	22–52	27–64	84° – 34°	53° – 19°30'	74° – 29°	9/12	7	22	0.92	0.28	0.24 (at 40mm)	Ring USM*2	77	3.3/83.5 x 3.8/96.8	1.1 lbs.	475	0.83–0.32	1.02–0.40	EW-83E	–	LP1319	NC	(0)
EF 20-35mm f/3.5-4.5 USM**	26–46	32–56	84° – 54°	62° – 38°	94° – 63°	11/12	5	22-27	1.1	0.34	0.13 (at 35mm)	Ring USM*2	77	3.3/83.5 x 2.7/96.8	11.9	340	0.70–0.36	1.00–0.80	EW-83II	–	LP1214	NC	(0)
EF-S 17-85mm f/4-5.6 IS USM	N/A	27–136	68°40' – 15°25'	48° – 10°25'	78°30' – 18°25'	12/17	6	22	1.1	0.35	0.20	Ring USM	67	3.1/78.5 x 3.6/92	1.1 lbs.	475	0.43–0.14	0.72–0.33	EW-73B	–	LP1116	NC	(0)
EF-S 18-55mm f/3.5-5.6 USM	N/A	29–88	65°30' – 23°20'	45°30' – 15°40'	74°20' – 27°50'	9/11	6	22-38	0.92	0.28	0.28 (at 55mm)	Ring USM II	58	2.7/69 x 2.6/66.2	6.7	190	0.81–0.23	0.92–0.51	EW-60C	–	LP814	(0)	(0)
EF-S 18-55mm f/3.5-5.6*	N/A	29–88	65°30' – 23°20'	45°30' – 15°40'	75°20' – 27°50'	9/11	6	22-38	0.92	0.28	0.28 (at 55mm)	MM	58	2.7/69 x 2.6/66.2	6.7	190	0.81–0.23	0.92–0.51	EW-60C	–	LP814	(0)	(0)
EF 24-70mm f/2.8L USM**	31–91	38–112	84° – 34°	53° – 19°30'	74° – 29°	13/16	8	22	1.25	0.38	0.29 (at 70mm)	Ring USM*2	77	3.3/83.2 x 4.9/123.5	2.1 lbs.	950	0.63–0.18	1.25–0.40	EW-83F	–	LP1219	(0)	(0)
EF 24-85mm f/3.5-4.5 USM**	31–111	38–136	74° – 24°	53° – 16°	84° – 28°30'	12/15	6	22-32	1.6	0.5	0.16 (at 85mm)	Ring USM*2	67	2.9/73 x 2.7/69.5	13.4	380	0.59–0.15	1.23–0.33	EW-73II	–	LP1014	NC	(0)
EF 28-80mm f/3.5-5.6 II	36–104	45–128	75° – 30°	46° – 17°	65° – 25°	10/10	5	22-38	1.25	0.38	0.26 (at 80mm)	MM*2	58	2.6/67 x 2.8/71	7.8	200	0.57–0.16	1.14–0.35	EW-60C	–	LP814	(0)	(0)
EF 28-90mm f/4-5.6 II USM	36–117	45–144	65° – 22°40'	46° – 15°10'	75° – 27°	8/10	5	22-32	1.3	0.38	0.30 (at 90mm)	Micro USM*2	58	2.6/67 x 2.8/71	6.7	190	0.56–0.14	1.13–0.31	EW-60C	–	LP814	(0)	(0)
EF 28-90mm f/4-5.6 III	36–117	45–144	65° – 22°40'	46° – 15°10'	75° – 27°	8/10	5	22-32	1.3	0.38	0.30 (at 90mm)	MM	58	2.6/67 x 2.8/71	6.7	190	0.56–0.14	1.13–0.31	EW-60C	–	LP814	(0)	(0)
EF 28-105mm f/3.5-4.5 II USM**	36–136	45–168	65° – 19°20'	46° – 13°	75° – 23°20'	12/15	7	22-27*4	1.6	0.5	0.19 (at 105mm)	Ring USM*2	58	2.8/72 x 3/75	13.1	375	0.53–0.12	0.75–0.27	EW-63II	–	LP814	(0)	(0)
EF 28-105mm f/4-5.6 USM**	36–136	45–168	65° – 19°20'	46° – 13°	75° – 23°20'	9/10	6	22-32	1.57	0.48	0.19 (at 105mm)	Micro USM*2	58	2.6/67 x 2.7/68	7.4	210	0.54–0.12	1.11–0.27	EW-63B	–	LP814	(0)	(0)
EF 28-135mm f/3.5-5.6 IS USM**	36–176	42–216	65° – 15°	46° – 10°	75° – 18°	12/16	6	22-36	1.64	0.5	0.19 (at 135mm)	Ring USM*2	72	3.1/78.4 x 3.8/96.8	1.2 lbs.	540	0.53–0.09	1.09–0.21	EW-78BII	–	LP1116	(0)	(0)
EF 28-200mm f/3.5-5.6 USM**	36–260	45–320	65° – 6°	46° – 7°	75° – 12°	12/16	6	22-36	1.5	0.45	0.28 (at 200mm)	Micro USM*2	72	3.1/78.4 x 3.5/96.8	1.1 lbs.	500	0.54–0.06	1.10–0.14	EW-78D	–	LP1116	NC	(0)
EF 35-80mm f/4-5.6 III	46–104	56–128	54° – 25°	38° – 17°	63° – 30°	8/8	5	22-32	1.3	0.4	0.23 (at 80mm)	MM*2	52	2.6/65 x 2.5/63.5	6.2	175	0.50–0.16	0.97–0.35	EW-54II	–	LP814	(1)	(1)
EF 28-300mm f/3.5-5.6L IS USM	36–390	45–480	65° – 6°50'	46° – 4°35'	75° – 8°15'	16/22	8	38	2.3	0.7	0.30 (at 300mm)	Ring USM*2	77	3.6/92 x 7.2/184	3.7 lbs.	1,670	0.50–0.04	0.50–0.09	EW-83G	–	LZ1324	NC	(6)
EF 55-200mm f/4.5-5.6 II USM	72–260	88–320	36° – 10°	25° – 7°	43° – 12°	13/13	6	22-29	3.9	1.2	0.17	Micro USM	52	3.4/86.2 x 7.8/197	10.9	310	0.22–0.06	0.41–0.14	ET-54	–	LP1016	(0)	(1)
EF 70-200mm f/2.8L IS USM**	91–260	112–320	29° – 10°	19°30' – 7°	34° – 12°	18/-23	8	32	4.6	1.4	0.16 (at 200mm)	Ring USM*2	77	7.3/84.6 x 7.6/193.6	3.2 lbs.	1,470	0.22–0.06	0.41–0.14	ET-86	–	LZ1324	(2)	(2)
EF 70-200mm f/2.8L USM**	91–260	112–320	29° – 10°	19°30' – 7°	34° – 12°	15/18	8	32	4.9	1.5	0.21 (at 200mm)	Ring USM*2	77	3/76 x 6.8/172	2.9 lbs.	1,310	0.23–0.06	0.39–0.13	ET-83II	–	LZ1324	(2)	(3)
EF 70-200mm f/4L USM**	91–260	112–320	29° – 10°	19°30' – 7°	34° – 12°	13/16	8	32	3.9	1.2	0.26 (at 300mm)	Ring USM*2	67	3.1/78.5 x 5.4/137.2	1.6 lbs.	705	0.21–0.04	0.39–0.09	ET-74	–	LP1224	(5)	(4)
EF 70-300mm f/4.5-5.6 DO IS USM**	91–390	112–480	29° – 6°50'	19°30' – 4°35'	34° – 8°15'	12/18	6	32-38	4.6	1.4	0.19 (at 300mm)	Ring USM*2	58	3.2/82.4 x 3.9/99.9	1.6 lbs.	720	0.26–0.04	0.46–0.09	ET-65B	–	LP1116	(4)	(4)
EF 75-300mm f/4-5.6 IS USM	98–390	120–480	27° – 6°50'	18°11' – 4°35'	32°11' – 8°15'	10/15	8	32-45	4.9	1.5	0.26 (at 300mm)	Micro USM	58	3.1/78.5 x 5.4/137.2	1.4 lbs.	650	0.21–0.04	0.39–0.09	ET-64II	–	LP1022	(5)	(4)
EF 75-300mm f/4-5.6 III USM	98–390	120–480	27° – 6°50'	18°11' – 4°35'	32°11' – 8°15'	9/13	7	32-45	4.9	1.5	0.25 (at 300mm)	Micro USM	58	2.8/71 x 4.8/122	1.1 lbs.	480	0.21–0.04	0.39–0.09	ET-60	–	LP1019	(5)	(4)
EF 75-300mm f/4-5.6 III	98–390	120–480	27° – 6°50'	18°11' – 4°35'	32°11' – 8°15'	9/13	7	32-45	4.9	1.5	0.25 (at 300mm)	MM*3	58	2.8/71 x 4.8/122	1.1 lbs.	480	0.21–0.04	0.39–0.09	ET-60	–	LP1019	(5)	(4)
EF 100-300mm f/4.5-5.6 USM**	130–390	160–480	20° – 6°50'	14° – 4°35'	24° – 8°15'	10/13	8	32-38*4	4.9	1.5	0.20 (at 300mm)	Ring USM*2	58	2.9/73 x 4.8/121.5	1.2 lbs.	540	0.26–0.04	0.37–0.09	ET-65III	–	LP1019	(5)	(4)
EF 100-400mm f/4.5-5.6L IS USM**	130–520	160–640	20° – 5°10'	14° – 3°30'	24° – 6°10'	14/17	8	32-38*4	5.9	1.8	0.20 (at 400mm)	Ring USM*2	77	3.6/92 x 7.4/189	3.0 lbs.	1,360	0.19–0.03	0.35–0.07	ET-83C	–	LZ1324	(4)	(5)
EF 14mm f/2.8L USM**	18	22	104°	81°	114°	10/14	5	22	0.8	0.25	0.10	Ring USM*2	Gelatin	3/77 x 3.5/89	1.2 lbs.	560	–	–	Built-in	–	LP1016	NC	NC
EF 15mm f/2.8 Fisheye	20	24	141°54'	91°44'	180°	7/8	5	22	0.7	0.2	0.14	AFD	Gelatin	2.9/73 x 2.4/62.2	11.6	330	0.94–0.80	–	Built-in	–	LP814	NC	NC
EF 20mm f/2.8 USM**	26	32	84°	62°	94°	9/11	5	22	0.8	0.25	0.14	Ring USM*2	72	3.1/77.5 x 2.8/70.6	14.3	405	0.72–0.60	–	EW-75II	–	LP1214	NC	NC
EF 24mm f/1.4L USM**	31	38	74°	53°	84°	9/11	7	22	0.82	0.25	0.16	Ring USM*2	77	3.3/83.5 x 3/77.4	1.2 lbs.	550	0.66–0.50	–	EW-83DII	–	LP1214	NC	(0)
EF 24mm f/2.8	31	38	74°	53°	84°	10/10	6	22	0.8	0.25	0.16	AFD	58	2.7/67.5 x 1.9/48.5	9.5	270	0.64–0.50	1.22–1.11	EW-60II	–	LP811	(0)	(0)
EF 28mm f/1.8 USM**	36	45	65°	46°	75°	9/10	7	22	0.8	0.25	0.18	Ring USM*2	58	2.9/73.6 x 2.2/55.6	10.9	310	0.61–0.43	1.13–0.96	EW-63II	–	LP814	(0)	(0)
EF 28mm f/2.8	36	45	65°	46°	75°	5/5	5	22	1.0	0.3	0.13	AFD	52	2.7/67.4 x 1.7/42.5	6.5	185	0.56–0.43	1.09–0.95	EW-65II	–	LP1011	(1)	(1)
EF 35mm f/1.4L USM**	45	56	54°	38°	63°	9/11	8	22	0.98	0.3	0.18	Ring USM*2	72	3.1/79 x 4.1/103	1.3 lbs.	580	0.54–0.36	0.97–0.79	EW-78C	–	LP1214	NC	(0)
EF 35mm f/2	45	56	54°	38°	63°	5/7	5	22	0.8	0.25	0.23	AFD	52	2.7/67.4 x 1.7/42.5	7.4	210	0.58–0.35	1.00–0.77	EW-65II	–	LP1011	(2)	(2)
EF 50mm f/1.4 USM	65	80	40°	27°	46°	6/7	8	22	1.5	0.45	0.15	Micro USM*2	58	2.9/73.8 x 2/50.5	10.2	290	0.39–0.24	0.68–0.53	ES-71II	–	LP1014	(2)	(2)
EF 50mm f/1.8 II	65	80	40°	27°	46°	5/6	5	22	1.5	0.45	0.15	MM*3	52	2.7/68.2 x 1.6/41	4.6	130	0.39–0.24	0.68–0.53	ES-62a#	–	LP1014	(2)	(1)
EF 85mm f/1.2L USM	111	136	24°	16°	28°30'	7/8	8	16	3.1	0.95	0.11	Ring USM	72	3.6/91.5 x 3.3/84	2.3 lbs.	1,025	0.25–0.15	0.42–0.33	ES-79II	–	LP1219	(5)	(5)
EF 85mm f/1.8 USM	111	136	24°	16°	28°30'	7/9	8	22	2.8	0.85	0.13	Ring USM*2	58	3/75 x 2.8/71.5	15.0	425	0.27–0.15	0.44–0.32	ET-65III	–	LP1014	(5)	(4)
EF 100mm f/2 USM**	130	160	20°	14°	24°	6/8	8	22	3.0	0.9	0.14	Ring USM*2	58	3/75 x 2.9/73.5	1.0 lbs.	460	0.27–0.13	0.42–0.28	ET-65III	–	LP1014	(5)	(4)
EF 135mm f/2L USM**	175	216	15°	10°	18°	8/10	8	32	3.0	0.9	0.19	Ring USM*2	72	3.2/82.5 x 4.4/112	1.6 lbs.	750	0.29–0.09	0.41–0.20	ET-78II	–	LP1219	(5)	(5)
EF 135mm f/2.8 w/ Softfocus	175	216	15°	10°	18°	6/7	6	32	4.3	1.3	0.12	AFD	52	2.7/69.2 x 3.9/98.4	13.8	390	0.22–0.09	0.33–0.20	ET-65III	–	LP1016	(5)	(4)
EF 200mm f/2.8L II USM**	260	320	10°	7°	12°	7/9	8	32	4.9	1.5	0.16	Ring USM*2	72	3.3/83.2 x 5.4/136.2	1.6 lbs.	765	0.23–0.06	0.32–0.14	ET-83BII	–	LP1222	(5)	(5)
EF 300mm f/2.8L IS USM**	390	480	6°50'	4°35'	8°15'	13/17	8	32	8.2	2.5	0.13	Ring USM*2	52 DI	5/128 x 9.9/252	5.6 lbs.	2,550	0.18–0.04	0.24–0.09	ET-120	Lens Case 300	–	NC	NC
EF 300mm f/4L IS USM**	390	480	6°50'	4°35'	8°15'	11/15	8	32	4.9	1.5	0.24	Ring USM*2	77	3.5/90 x 8.7/221	2.6 lbs.	1,190	0.30–0.04	0.37–0.09	Built-in	–	LZ1128	(5)	(5)
EF 400mm f/2.8L IS USM**	520	640	5°10'	3°30'	6°10'	13/17	8	32	9.8	3.0	0.15	Ring USM*2	52 DI	6.4/163 x 13.7/349	11.7 lbs.	5,300	0.19–0.03	0.23–0.06	ET-155	Lens Case 400	–	NC	(0)
EF 400mm f/4 DO IS USM**	520	640	5°10'	3°30'	6°10'	13/17	8	32	11.48	3.5	0.12	Ring USM	52 DI	5/128 x 9.4/232.7	4.3 lbs.	1,940	0.16–0.03	0.20–0.07	ET-120	Lens Case 400B	–	NC	(0)
EF 400mm f/5.6L USM**	520	640	5°10'	3°30'	6°10'	6/7	8	32	11.5	3.5	0.12	Ring USM*2	77	3.5/90 x 10.1/256.5	2.8 lbs.	1,250	0.16–0.03	0.21–0.07	Built-in	–	LZ1132	(5)	(5)
EF 500mm f/4L IS USM**	650	800	4°	2°45'	5°	13/17	8	32	14.8	4.5	0.12	Ring USM*2	52 DI	5.8/146 x 15.2/387	8.5 lbs.	3,870	0.15–0.03	0.18–0.05	ET-138	Lens Case 500	–	NC	NC
EF 600mm f/4L IS USM**	780	960	3°30'	2°20'	4°10'	13/17	8	32	18.0	5.5	0.12	Ring USM*2	52 DI	6.6/168 x 18/456	11.8 lbs.	5,360	0.14–0.02	0.17–0.05	ET-160	Lens Case 600	–	NC	NC
EF 1200mm f/5.6L USM**	1560	1920	1°45'	1°10'	2°05'	10/13	8	32	45.9	14.0	0.09	Ring USM	48 DI	9/228 x 32.9/836	36.4 lbs.	16,500	0.12–0.01	0.13–0.02	Built-in	Exclusive	–	NC	NC
EF 50mm f/2.5 Compact Macro	65	80	40°	27°	46°	8/9	6	32	0.8	0.23	0.50	AFD	52	2.7/67.6 x 2.5/63	9.9	280	0.74–0.24	1.04–0.54	Built-in	–	LP814	(2)	(2)
Life Size Converter EF	–	–	–	–	–	3/4	–	–	0.8	0.24	1.00	–	–	2.7/67.6 x 1.4/34.9	5.6	160	–	–	–	–	LP811	(5)*5	(5)*5
MP-E 65mm f/2.8 1-5x Macro**	85	104	15°40'	10°35'	18°40'	8/10	6	16	0.8	0.24	5.00	–	58	3.2/81 x 1.4/34.9	1.6 lbs.	730	–	–	–	–	LP1216	(0)	(0)
EF-S 60mm f/2.8 Macro USM NEW	–	96	21º	14º	25º	8/12	7	32	0.65	0.2	1.00	Ring USM	52	2.9/73 x 2.8/69.8	11.8	335	1.28–0.20	1.61–0.44	ET-67B	–	LP1016	(6)	(6)
EF 100mm f/2.8 Macro USM**	130	160	20°	14°	24°	8/12	8	32	1.0	0.31	1.00	Ring USM*2	58	3.1/79 x 4.7/119	1.3 lbs.	600	1.19–0.12	1.39–0.26	ET-67	–	LP1219	(4)	(4)
EF 180mm f/3.5L Macro USM**	234	288	11°25'	7°40'	13°40'	12/14	8	32	1.6	0.48	1.00	Ring USM*2	72	3.2/82.5 x 7.3/186.6	2.4 lbs.	1,090	10.9–0.07	1.21–0.15	ET-78II	–	LZ1324	(5)	(5)
TS-E 24mm f/3.5L	31	38	74° – 53°	84°	w/o tilt or shift	9/11	8	22	1.0	0.3	0.14	–	72	3.1/78 x 3.4/86.7	1.2 lbs.	570	0.62–0.49	1.21–1.10	EW-75BII	–	LP1216	NC	(0)
TS-E 45mm f/2.8	59	72	44° – 33°	51°	w/o tilt or shift	9/10	8	22	1.3	0.4	0.16	–	72	3.2/81 x 3.5/90.1	1.4 lbs.	645	0.44–0.27	–	EW-79BII	–	LP1216	NC	(2)
TS-E 90mm f/2.8	117	144	22°37' – 15°11'	27°	w/o tilt or shift	5/6	8	32	1.6	0.5	0.29	–	58	2.9/73.6 x 1.1/27.2	1.2 lbs.	565	0.43–0.14	0.60–0.31	ES-65II	–	LP1016	(5)	(4)
Extenders EF 1.4x II	–	–	–	–	–	–	–	–	–	–	–	–	–	2.9/72.8 x 1.1/27.2	7.8	220	–	–	–	–	LP811	–	–
Extenders EF 2x II	–	–	–	–	–	–	–	–	–	–	–	–	–	2.8/71.8 x 2.3/57.9	9.3	265	–	–	–	–	LP811	–	–
Extension Tube EF 12 II	–	–	–	–	–	6	–	–	–	–	–	–	–	2.6/66.5 x 0.5/12.3	2.3	66	–	–	–	–	Exclusive	–	–
Extension Tube EF 25 II	–	–	–	–	–	7	–	–	–	–	–	–	–	2.6/66.5 x 1.1/27.3	3..4	95	–	–	–	–	LP811	–	–

*Available only with EOS Digital Rebel XT, Digital Rebel and EOS 20D lens kits, can be mounted ONLY on EOS Digital Rebel XT, Digital Rebel and 20D. **Incorporates distance information with E-TTL II. ***Angle of view for EF-S lenses is stated for APS-C format.

Extender EF 1.4x II

Lens Attachment		EF 135mm f/2L USM	EF 180mm f/3.5L Macro USM	EF 200mm f/1.8L USM	EF 200mm f/2.8L II USM	EF 300mm f/2.8L IS USM	EF 300mm f/4L IS USM	EF 400mm f/2.8L IS USM	EF 400mm f/4 DO IS USM
Focal Length (mm)		189	252	280	280	420	420	560	560
Apparent Length	APS-H	246	328	364	364	546	546	728	728
	APS-C	302	403	448	448	672	672	896	896
f-stop (f)		2.5-45	4.5*4-45	2.5-32	2.5-32	4-45	5.6-45	4-45	5.6-45
Max. Magnification		0.27	1.40	0.12	0.22	0.15	0.33	0.22	0.17
AF		○	○*10	○	○	○	○	○	○

Lens Attachment		EF 400mm f/5.6L USM	EF 500mm f/4L IS USM	EF 600mm f/4L IS USM	EF 1200mm f/5.6L USM	EF 70-200mm f/2.8L IS USM	EF 70-200mm f/2.8L USM	EF 70-200mm f/4L USM	EF 100-400mm f/4.5-5.6L IS USM
Focal Length (mm)		560	700	840	1,680	98-280	98-280	98-280	140-560
Apparent Length	APS-H	728	910	1.092	2,184	127-364	127-364	127-364	182-728
	APS-C	896	1,120	1,344	2,688	157-448	157-448	157-448	224-896
f-stop (f)		8-45	5.6-64	5.6-64	8-45	4-45	4-45	5.6-45	6.7-54*4
Max. Magnification		0.18	0.17	0.17	0.12	0.22	0.24	0.31	0.28
AF		○*11	○	○	×	○*9	○	○	○*11*12

Extender EF 2x II

Lens Attachment		EF 135mm f/2L USM	EF 180mm f/3.5L Macro USM	EF 200mm f/1.8L USM	EF 200mm f/2.8L II USM	EF 300mm f/2.8L IS USM	EF 300mm f/4L IS USM	EF 400mm f/2.8L IS USM	EF 400mm f/4 DO IS USM
Focal Length (mm)		270	360	400	400	600	600	800	800
Apparent Length	APS-H	351	468	520	520	780	780	1,040	1,040
	APS-C	432	576	640	640	960	960	1,280	1,280
f-stop (f)		4-64	6.7*4-64	3.5-45	5.6-64	5.6-64	8-64	5.6-64	8-64
Max. Magnification		0.38	2.00	0.18	0.32	0.28	0.47	0.31	0.24
AF		○	×	○	○	○	○*11*12	○	×

Lens Attachment		EF 400mm f/5.6L USM	EF 500mm f/4L IS USM	EF 600mm f/4L IS USM	EF 1200mm f/5.6L USM	EF 70-200mm f/2.8L IS USM	EF 70-200mm f/2.8L USM	EF 70-200mm f/4L USM	EF 100-400mm f/4.5-5.6L IS USM
Focal Length (mm)		800	1,000	1,200	2,400	140-400	140-400	140-400	200-800
Apparent Length	APS-H	1,040	1,300	1,560	3,120	182-520	182-520	182-520	260-1,120
	APS-C	1,280	1,600	1,920	3,840	224-640	224-640	224-640	320-1,280
f-stop (f)		11-64	8-90	8-90	11-64	5.6-64	5.6-64	8-64	9.5-76
Max. Magnification		0.27	0.27	0.27	0.27	0.27	0.27	0.27	0.27
AF		×	○*11*12	○*11*12	×	○*9	○	○*11	×*12

(○ = possible × = impossible)

*1. Maximum number of Hood III/IV attachable. In the case of zoom lenses, the maximum number applies to the shortest focal length.
*2. Mechanical full-time manual focusing built-in.
*3. Micro motor.
*4. Data based on EOS models with exposures displayed in 1/2 stop increments. It varies slightly with the EOS-1Ds Mark II, EOS-1Ds, EOS-1D Mark II, EOS-1D, EOS 20D, EOS 10D, Digital Rebel XT, Digital Rebel, EOS-1V, EOS-1N, EOS-1 and EOS-3.
*5. With EF 50mm f/2.5 Compact Macro.
*6. Extension Tube EF 12 can be used with EF lenses except the EF 14mm f/2.8L USM, 50mm f/1.0L USM, and lenses which cannot be focused manually.
*7. Extension Tube EF 25 can be used with EF lenses except the EF 14mm f/2.8L USM, 15mm f/2.8 Fisheye, 20mm f/2.8 USM, 24mm f/1.4L USM, 50mm f/1.0L USM, and most wide-angle zooms at the shorter focal lengths, as well as the TS-E 45mm, and lenses which cannot be focused manually.
*8. Image circle dia. 58.6mm.
*9. If the EF 70-200mm f/2.8L USM lens is attached to an EOS camera having multiple focusing points and an Extender is attached to the lens, only the center focusing point will be usable for AF.
*10. The autofocusing range is from 2.6 feet (0.8m) to infinity.
*11. With the EOS-1Ds Mark II, EOS-1D Mark II, EOS-1Ds, EOS-1D, EOS-1V and EOS-3, AF is possible with the center focusing point.
*12. The Image Stabilizer does not operate with the following cameras: EOS 650, 620, 630/600, RT, 700, 750, 850, EOS-1, A2/A2E, 10s, Elan, Rebel/Rebel S, Rebel II/Rebel SII.

NC : Not compatible with Gelatin Filter Holder III/IV.