

VERANDA 3
FULL SHADE
OUTDOOR TV



SMARTER BRIGHTER BETTER

The Veranda 3 is SunBrite's new full shade TV with Android TV, giving you access to over 700,000 movies and shows from your favorite apps. It features 1000 nits of brightness, Quantum dot color, and local zone dimming on a 120Hz panel for a premium outdoor cinematic experience.

CREATE AN OUTDOOR
EXPERIENCE TODAY

SunBriteTV.com



Start Streaming

With Android TV built in, you can cue the latest episode, pick up where you left off, or jump into a new show in no time. Even find music, games, and YouTube videos on your customizable home screen.



Ultra-Bright Picture

With 1000 nits of brightness. The Veranda 3 is up to 4x brighter than many indoor TVs. Plus, with 72 local dimming zones, it delivers outstanding contrast for a cinema-like outdoor experience.



Quantum Dot Color

Quantum Dot technology uses tiny phosphorescent crystals to produce over one billion colors for a more highly saturated and accurate color profile versus an average LCD or LED screen.

05052022 TS



SUNBRITE



Model Dimensions Comparison

	55" Model	65" Model	75" Model
LCD Screen	55-inch diagonal Color Active Matrix TFT LED LCD	65-inch diagonal Color Active Matrix TFT LED LCD	75-inch diagonal Color Active Matrix TFT LED LCD
Resolution	3840x2160 UHD 4k HDR	3840x2160 UHD 4k HDR	3840x2160 UHD 4k HDR
Aspect Ratio	16:9	16:9	16:9
Backlight Brightness	1000 nits (cd/m2)	1000 nits (cd/m2)	1000 nits (cd/m2)
Contrast Ratio	6000:1	6000:1	4000:1
Frame Rate	60Hz standard, 120Hz maximum	60Hz standard, 120Hz maximum	60Hz standard, 120Hz maximum
H/V Viewing Angle	178° by 178°	178° by 178°	178° by 178°
Response Time	8 milliseconds	8 milliseconds	8 milliseconds
TV formats	2160p (HDMI only), 1080p, 1080i, 720p, 720i, 480p, 480i	2160p (HDMI only), 1080p, 1080i, 720p, 720i, 480p, 480i	2160p (HDMI only), 1080p, 1080i, 720p, 720i, 480p, 480i
RF Input Connector	Antenna/CATV (NTSC/ATSC/QAM) x1	Antenna/CATV (NTSC/ATSC/QAM) x1	Antenna/CATV (NTSC/ATSC/QAM) x1
HDMI Input Connector	HDMI Input x4 (Supports HDMI 2.1, HDMI 2.0, HDMI 1.4, HDCP 1.4 & HDCP 2.2) (eARC on HDMI 3)	HDMI Input x4 (Supports HDMI 2.1, HDMI 2.0, HDMI 1.4, HDCP 1.4 & HDCP 2.2) (eARC on HDMI 3)	HDMI Input x4 (Supports HDMI 2.1, HDMI 2.0, HDMI 1.4, HDCP 1.4 & HDCP 2.2) (eARC on HDMI 3)
Video Composite Input Connector	Composite Video x1, L/R Audio Inputs x1 (Requires Adapter, not included)	Composite Video x1, L/R Audio Inputs x1 (Requires Adapter, not included)	Composite Video x1, L/R Audio Inputs x1 (Requires Adapter, not included)
Control Set	Discrete IR Control, Concealed rear IR receiver, IP Control	Discrete IR Control, Concealed rear IR receiver, IP Control	Discrete IR Control, Concealed rear IR receiver, IP Control
Audio Out	Toslink Optical audio (Fixed) / Analog 3.5mm (variable)	Toslink Optical audio (Fixed) / Analog 3.5mm (variable)	Toslink Optical audio (Fixed) / Analog 3.5mm (variable)
Speakers	20 Watt downfiring internal speakers (included) or optional speaker bar (not included)	20 Watt downfiring internal speakers (included) or optional speaker bar (not included)	20 Watt downfiring internal speakers (included) or optional speaker bar (not included)
Exterior	Powder-coated aluminum	Powder-coated aluminum	Powder-coated aluminum
Colors	Black only	Black only	Black only
Input Power	120 VAC, 60Hz 1.6A Max	120 VAC, 60Hz 2.1A Max	120 VAC, 60Hz 3.1A Max
Operating Temperature	-24° to 104° F. (-31° to 40° C)	-24° to 104° F. (-31° to 40° C)	-24° to 104° F. (-31° to 40° C)
Non-operating Temperature	-24° to 140° F. (-31° to 60° C)	-24° to 140° F. (-31° to 60° C)	-24° to 140° F. (-31° to 60° C)
Accessories Included	Weatherproof remote control with battery	Weatherproof remote control with battery	Weatherproof remote control with battery
TV Dimensions	49.75" W x 29.25" H x 4.25" D 1258mm W x 741mm H x 108mm D	58" W x 34" H x 4.25" D 1473mm W x 864mm H x 108mm D	67" W x 39" H x 4.25" D 1700mm W x 987mm H x 108mm D
TV Weight	47 lb. / 21.3 kg	60 lb. / 27.3 kg	89 lb. / 40.4 kg
Shipping Weight	62 lb. / 28.1 kg	78 lb. / 35.4 kg	107 lb. / 48.5 kg
Residential Warranty	1 year	1 year	1 year
Commercial Warranty	1 year	1 year	1 year
VESA Mount Pattern	400mm x 400mm	400mm x 400mm	400mm x 400mm