


CRS300/4

CRS performance, now available in a 1RU half-width design. Built to masterfully match the performance of existing Coastal Source CRS amplifiers while taking up less space in a rack than ever before.











CRS AMPLIFIER SPECIFICATIONS

Dimensions: 10.78" x 1.59" x 8.25" (275x40x210mm)

Weight: 5.75 lbs (2.6 kg)

Construction: Powder Coated Steel

Anodized Aluminum

Max Speakers: Up to 2 speakers per channel

and up to 1 sub total

Frequency Response at 8 ohms: 20Hz-20kHz +/- 0.5 dB

Idle Power: 18W

Power In: 100-240 VAC @ 50-60Hz

Power Out: 300W

Impedance: Stable to 4 ohms

Mounting: Rack Mount

Wiring: Coastal Connectors or Bare Wire (Phoenix)

Warranty: 5-Year Limited Warranty*



ORDERING INFORMATION

COMPATIBLE PRODUCTS

COT II / (TIBLE T T(CBCCTC			
SKU	ITEM		
JBX-PT	JBX CC Pass- through Box		
JBX-C	JBX CC Converter Box		
CRSRCAICA-PR	CRS RCA Input Pigtails		
CRSXLRICA-PR	CRS XLR Input Pigtails		
Cxx12/2WT	White 12AWG CC Extension Cables		

^{*}All Coastal Source products bear a 2-year limited warranty for commercial/non-residential installations.



p. 800.719.1996

info@coastalsource.com

coastalsource.com