QUICK REFERENCE GUIDE > RGV3-305-N

Gas Range, 30", 5 Burners

Series 7 | Professional

Stainless Steel | Natural gas



Professional style and performance, with high power burners delivering high heat or the most gentle simmer.

- Top burner heat of 23,500 BTU, for seriously fast boiling
- · Gas oven with 4.6 cu ft total capacity
- Non-tip full-extension shelves in main cavitiy for safe removal of hot dishes
- Made from quality materials and real stainless steel

DIMENSIONS

Height	35 3/4 - 36 3/4
Width	29 7/8
Depth	29 1/8

FEATURES & BENEFITS

COOKTOP POWER

Sealed Dual Flow Burners™ deliver cooktop power up to 22,500 BTU for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

COOKING FLEXIBILITY

The cooktop is designed for easy access to any burner with grates you can smoothly slide pots across. The oven is large enough to hold full size baking sheets.

DESIGN QUALITY

This range has craftsmanship in every detail, with real stainless steel, cast-iron grates, and titanium coated dials. Each cavity features incandescent lights and full extension telescopic racks. From the robust legs to the powerful cooktop, the Range is built to last.

EASY TO CLEAN

With a continuous, porcelain basepan, cleaning up spills is effortless. Your cooktop simply needs a quick wipe to keep it looking good as new.

TOTAL CONTROL

Precise control across high and low settings is delivered through the halo-illuminated cooktop dials.

SPECIFICATIONS

Accessories (sold separately)

Square handle option AH-R30

Burner ratings

Maximum burner power	23500 BTU
Power back left	18500BTU
Power back right	18500BTU
Power centre	23500BTU
Power front left	18500BTU
Power front right	18500BTU
Total cooktop power	97500 BTU

Capacity

Shelf positions	!
Total capacity	4.6cu f
Usable capacity	3.4cu f

Cleaning

Easy clean porcelain basepan	
------------------------------	--

Controls

Electric circuit	3 Wire
Metal illuminated dials	•

Gas Requirements

Fitting and pipe	½ NPT, min. ¾" 🛭 flex lin
Supply Pressure (natural gas)	6" to 9" W.0

Oven features

Auto re-ignition system	•
Broil pan	•
Electronic oven control	•
Full extension telescopic	

QUICK REFERENCE GUIDE > RGV3-305-N Date: 28.04.2023 > 2

Infrared Broiler		
Internal light		
Titanium coated, illuminated	•	
Oven functions		
Bake	•	
Broil	•	
Convection bake	•	
Number of functions	4	
Slow cook	•	
Oven performance		
Bake power	21,000 BTU	
Broil power	18,500 BTU	
Power requirements		
Amperage	15A	
Rated current	15A	
Supply frequency	60Hz	
Product dimensions		
Depth	29 1/8"	
Height	35 3/4 - 36 3/4"	
Width	29 7/8"	
Rangetop features		
Sealed range top	•	
Vent trim included	•	

Combustible situation	BGRV3-3030H
Non combustible situation	BGRV2-3030 / BGRV2-1230
Recommended hood	HCB30-6_N (Professional
Safety	
ADA compliant	•
Full extension telescopic	•
SKU	82006

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com



User Guide



Service & Warranty



Installation Guide



Recommended Back Guards Ventilation