

Photometrics (at 5,600K / 100% brightness):

3,600 lux at 1.64' / 0.5 m

1,040 lux at 3.28' / 1 m

160 lux at 9.84' / 3 m

Luminous Flux (lumens): 2,600 lm +/- 250 lm

Brightness Adjustment: 1 - 100%

Color Temperature: 2,500K - 8,500K +/- 200K

Color Accuracy: TLCI 98+ & CRI 96+

Beam Angle: 120-degrees

Batteries: NP-F x 2 or D-Tap x 1 (not included)

Fixture Mount: 5/8" Receiver

Remote Operation:

Wireless Connection: Bluetooth (registered trademark)

Controller: ProMaster Light Attendant app

Groups: A, B, & C + All

Channels: 1 - 15 + All

Operational Range: 49' / 15

Maximum Power Consumption: 50 W

Cooling System: Passive

Working Temperature: 32 - 95 F / 0 - 35 F

Dimensions:

15 1/8" x 10 3/4" x 2" | 38.4 cm x 27.3 cm x 5.1 (without barn doors or light stand adapter)

15 1/8" x 14 3/4" x 2 7/8" | 38.4 cm x 37.5 cm x 7.3 cm (with barn doors and light stand adapter)

Weight:

3 lbs 5 oz | 1.5 kg (without barn doors or light stand adapter)

5 lbs | 2.27 kg (with barn doors and light stand adapter)

**Stand Specifications:**

Maximum working height: 75 1/2" / 191.8cm

Minimum working height: 16 1/2" / 41.9cm

Folded length: 16" / 40.6cm

Weight: 2 lbs 10 oz / 1.19 kg

Maximum load: 6.6 lbs / 3 kg

**Kit Includes:**

2 Ultrasoft US1014RGB lights

2 LS-CT light stands

2 barn door assemblies (4 panels each)

2 AC power adapters

2 D-Tap power cables

1 Transport case with foam inserts

2 Fabric dividers (alternative to foam inserts)