

## Temperature / Pressures

|                                |             |
|--------------------------------|-------------|
| Maximum Operating Temperature: | 125 DegreeF |
|--------------------------------|-------------|

|                             |          |
|-----------------------------|----------|
| Maximum Operating Pressure: | 250 psig |
|-----------------------------|----------|

|                                |          |
|--------------------------------|----------|
| Maximum Differential Pressure: | 100 psid |
|--------------------------------|----------|

|                    |          |
|--------------------|----------|
| Collapse Pressure: | 200 psid |
|--------------------|----------|

## Specifications

|             |        |
|-------------|--------|
| Part Number | FI-PB1 |
|-------------|--------|

|               |               |
|---------------|---------------|
| O.D. x Length | 2.50" x 9.75" |
|---------------|---------------|

|        |         |
|--------|---------|
| Weight | 0.85 lb |
|--------|---------|

|                   |                       |
|-------------------|-----------------------|
| Chlorine Capacity | >6,000 gal @ 0.75 GPM |
|-------------------|-----------------------|

|                             |                   |
|-----------------------------|-------------------|
| Normal $\mu\text{m}$ Rating | 0.5 $\mu\text{m}$ |
|-----------------------------|-------------------|

|                |                       |
|----------------|-----------------------|
| Lead Reduction | 2,500 gal. @ 0.75 GPM |
|----------------|-----------------------|

|                                 |                     |
|---------------------------------|---------------------|
| Initial $\Delta\text{P}$ @ Flow | 4.0 psid @ 0.75 GPM |
|---------------------------------|---------------------|