

Stinger ix212 HORIZON12

SRX-GM14128

Radio Replacement Kit for select
2014-2019 Silverado/Sierra Trucks

Introduction and Features

The SRX-GM14128 is a complete radio replacement kit for the installation of the Stinger ix212 modular radio in Chevrolet Silverado and GMC Sierra trucks. All modules, cables and adapters are included to retain important features of the factory system, including: OnStar, front and rear park assist, warning chimes, factory reverse camera, steering wheel-mounted radio controls and AM/FM reception. Plug & Play wiring harnesses allow for quick and easy installation without the need to cut or splice any wiring. The display mounting panel allows flush mounting the 12 inch display without modifying/cutting any part of the vehicle's sub-dash.

Important Notes

We recommend reading this manual thoroughly to familiarize yourself with the entire process prior to beginning the installation.

1. **Does not** retain the following factory features:
 - Factory satellite radio
 - Valet Mode
 - Rear seat entertainment system (RSE)
 - Teen Driver Features
 - Time of Day in Cluster
 - OnStar Text
 - Factory USB Ports
 - Wi-Fi
2. If installing aftermarket amplifiers, the included RPA-SPK can be used to retain OnStar/chimes.
3. Chime volume can be adjusted in the ix212 settings
4. The Voice button can be set to activate the factory OnStar function when pressed for longer than 1.5 seconds or given the ability to control the aftermarket radio. This option can be found in the Installer Settings on the ix212. By default, this feature is set to control the aftermarket radio, but OnStar can still be accessed by using the mirror controls.
5. For the HORIZON12 Display to be waterproof, you must install 6 waterproof plugs to the back of the touch panel display in the screw holes not used for mounting.
6. This guide is applicale to ix212 (HORIZON12) radios.

Stinger ix212 HORIZON12

SRX-GM14128

Radio Replacement Kit for select
2014-2019 Silverado/Sierra Trucks

Recommended Tools


Plastic Panel Tool
7mm Socket
10mm Socket

Ratchet
Torx T15 Screwdriver
Small Flat-blade Screwdriver

Pick Tool
Wire Feeder
Power Screwdriver

Included Components

1. Display Mounting Panel
2. Main Frame Assembly
3. Dual USB Extension (SSUSB3)
4. AM / FM Antenna Adapter (BAA22)
5. Main Harness Adapter (SR-SRK-ADAPT-IX2XXV2)
6. Main Harness (SRK-GM14HX-HAR V1)
7. Vehicle Harness Adapter (GM52-ADAPT)
8. Radio Replacement Interface (GM6A-SRK)
9. Steering Wheel Control Harness (GM5LIN-SW-HAR)
10. Factory Rear Camera Adapter (CAM-GM51-HAR)
11. IOB Display Harness (GM5CAM-DIS-HAR)
12. MOST Loops (MOST Loop 1 / MOST Loop 2)
13. External Chime Speaker (RPA-SPK)
14. Differential Video Adapter (RPA-VA1)
15. Satellite Antenna Adapter (SAT-01)
16. Side Mounting Brackets (L & R)
17. PAC-Link Cable (10P-2-10P-6-HAR_V1)
18. PAC-Link Module (PL1)
19. Screw, M5 X10 PHP (Black) x4 (Not Shown)
20. Screw, #8 X 0.5" Tapping PHP x2 (Not Shown)
21. GPS Antenna
22. ix212 Camera Harness
23. ix212 Data Harness
24. ix212 AV Harness
25. External Mic (Not Shown)




NOTE: Along with the SRX-GM14128 components,
additional mounting clips for Main Frame Assembly
(Not Shown)

Stinger ix212 HORIZON12

SRX-GM14128
Radio Replacement Kit for select
2014-2019 Silverado/Sierra Trucks

Wiring Overview



Stinger ix212 HORIZON12

SRX-GM14128

Radio Replacement Kit for select
2014-2019 Silverado/Sierra Trucks

Factory Radio Code

Before starting, determine the vehicle's factory audio system by referencing the Service Parts Identification sticker inside the upper glove box.

One of these RPO codes will be listed:

IO3, IO4, IO5, IO6 or IOB

The installations are very similar for each type of factory audio system, but there are differences referenced throughout this guide.

Note: The installation shown in this guide is IO5 with factory rear camera and steering wheel controls.



This installation manual will cover the necessary order of procedures to complete the installation efficiently and to avoid redoing any steps. The order will be as follows; Disassembly, In-Vehicle Harness Connections and Preparation, Interface and Main Harness Connections, Display Mounting Panel Preparation, Radio Module Preparation and Radio Unit Installation.

The installation steps shown are all required for full functionality of the radio. If adding additional components; cameras, amplifiers, satellite radio, etc., additional steps and harnesses will be needed.

Section 1: Disassembly

Part One: Center Dash Disassembly



Step 1

Remove the radio display/climate control trim panel using a plastic trim tool to release the retaining clips. Unplug any wire harnesses from the back of the trim panel, if equipped.



Step 2

Remove the four 7mm screws securing the radio display/climate control panel. Pull outward to release the retaining clips. Remove all connectors from the back of the panel.



Step 3

If equipped, remove the two 7mm screws from the CD/DVD mechanism, remove and unplug. Connect one of the included MOST Loops to this connector and tuck into the dash.


Stinger ix212 HORIZON12

SRX-GM14128

Radio Replacement Kit for select
2014-2019 Silverado/Sierra Trucks


Section 1: Disassembly (Continued)

Part One: Center Dash Disassembly (Continued)



Step 4

Unplug all connectors and cables from the upper radio module shown.



Step 5

Remove the upper radio module by pushing upward on the locking clip and pulling outward on the module.

Part Two: Lower Storage Compartment Removal



Step 1

Remove the two Torx T15 screws from the bottom edge of the storage compartment.



Step 2

Remove the upper Torx T15 screw inside the storage compartment.



Step 3

Using a panel tool or similar, release the top retaining clips and remove the storage assembly.

Stinger ix212 HORIZON12

SRX-GM14128

Radio Replacement Kit for select
2014-2019 Silverado/Sierra Trucks

Section 1: Disassembly (Continued)

Part Three: Glove Box Removal (Optional)

If the vehicle is equipped with IO4, IO5 or IO6 radio AND a factory rear camera, follow the steps below to remove the glove box. For IO3 and IOB vehicles, or no factory rear camera, proceed to Part Four.



Step 1

Remove the two Torx T15 screws from the bottom edge of the lower glove box.



Step 2

Open the upper and lower glove box doors and remove the two Torx T15 screws securing the lower glove box.



Step 3

Pull outward on the lower glove box to release the retaining clips and remove the lower glove box.



Step 4

Remove the two Torx T15 screws and pull to remove the upper glove box. Unplug the factory USB port from the backside.



Step 5

Up, behind the metal bar running across the inner dash, locate the HMI Module; black module with multiple colored plugs facing down.



Step 6

Unplug the gray 12 pin camera harness from the HMI module.

Stinger ix212 HORIZON12

SRX-GM14128

Radio Replacement Kit for select
2014-2019 Silverado/Sierra Trucks

Section 1: Disassembly (Continued)

Part Four: A Pillar Removal



Step 1

Remove the inserts covering the bolts on the passenger A pillar handle.



Step 2

Remove the two 10mm bolts.




Step 3

Pull the trim panel to release the retaining clips and remove.

Part Five: Lower Steering Column Cover Removal (Optional)

If the vehicle is equipped with IO3, IO4, IO5 or IO6 radio AND steering wheel controls, follow the steps below to remove the lower steering column cover. For IOB vehicles or no steering wheel controls, proceed to Section Two on next page.



Step 1

Remove the two Torx T15 screws from the bottom edge of knee panel below the steering column. Pull outward to remove the panel and lay carefully on the floor board.



Step 2

Remove the plastic handle from the steering wheel tilt lever by pulling outward, towards the driver's door on the handle. A trim tool may also be used if unable to remove by hand.



Step 3

Pull downward on the lower cover on both sides to release the locking tabs and remove the lower cover.

Stinger ix212 HORIZON12

SRX-GM14128

Radio Replacement Kit for select
2014-2019 Silverado/Sierra Trucks

Section 2: In-Vehicle Harness Connections and Preparation

Part Six: External Speaker Installation



Step 1

Place External Speaker bracket behind black plastic knee panel support.



Step 2

Align right side hole of the speaker bracket with the hole located in the support and zip tie. Place a second zip tie around the support and speaker bracket.



Step 3

Route external speaker cable to the radio opening.

Note: The **External Speaker** is only required when running an aftermarket amplifier connected to the radio's RCA preamp outputs. Vehicles with **Bose** or **No Amplifier** do not require installation of the External Speaker. Vehicles running only a subwoofer amplifier **do not** require installation of the **External Speaker**.

Stinger ix212 HORIZON12

SRX-GM14128

Radio Replacement Kit for select
2014-2019 Silverado/Sierra Trucks

Section 2: In-Vehicle Harness Connections and Preparation (Continued)

Part One: Dual USB Extension (SSUSB3)

Firmware Updates require access to a USB port. The **SSUSB3** is designed to extend the USB ports on the back of the ix212 to where they are accessible once the radio is installed.

For this installation, the factory 12V power outlet will be replaced with the **SSUSB3**. You may choose to follow these steps, or mount the USB port somewhere else in the vehicle. Please note, the factory USB ports will no longer function after the factory radio is removed.



Step 1

From the backside of the lower storage compartment, remove the metal insert from the power outlet by releasing the two retaining clips with a small pick and pushing out the front side.



Step 2

Remove the plastic sleeve by depressing the two tabs and pushing out the front.



Step 3

Install the optional USB cover and feed the USB cables through the front of the panel. Secure with the flanged nut and then lock with the lock nut.



Step 4

Route the USB cables up and out of the right side opening at the rear of the CD/DVD opening.

Stinger ix212 HORIZON12

SRX-GM14128

Radio Replacement Kit for select
2014-2019 Silverado/Sierra Trucks

Section 2: In-Vehicle Harness Connections and Preparation (Continued)

Part Two: Factory Rear Camera Retention Harness (CAM-GM51-HAR)

If the vehicle is equipped with IO4, IO5 or IO6 radio AND a factory rear camera, follow the steps below to install the factory camera retention harness at the HMI module behind the glove box. For IO3 and IOB vehicles, or no factory rear camera, proceed to Part Four.




Step 1

Plug the gray 12 pin camera harness from the HMI module into the **CAM-GM51-HAR**.



Step 2

Route the yellow RCA end of the camera cable to the radio opening. Secure plug and cable with zip ties.



Step 3

Route the camera RCA out of the left side opening at the rear of the CD/DVD opening.

Part Three: Steering Wheel Control (SWC) Retention Harness (GM5LIN-SW-HAR)

If the vehicle is equipped with IO4, IO5 or IO6 radio AND steering wheel controls, follow the steps below to install the SWC retention harness at the steering column. For IO3 and IOB vehicles, or no steering wheel controls, proceed to Part Four.



Step 1

Locate and unplug the black 10 pin connector located on the underside of the steering column.



Step 2

Plug the male connector into the female end of the **GM5LIN-SW-HAR** and plug the **GM5LIN-SW-HAR** male end into the female connector on the steering column.



Step 3

Secure the T-harness to the factory wire harness. Route the 50" single lead from the **GM5LIN-SW-HAR** to the radio opening, securing with zip ties.

Stinger ix212 HORIZON12

SRX-GM14128

Radio Replacement Kit for select
2014-2019 Silverado/Sierra Trucks

Section 2: In-Vehicle Harness Connections and Preparation (Continued)

Part Three: Steering Wheel Control (SWC) Retention Harness (Continued)




Step 4

Route the steering wheel control lead into the CD/DVD area through the left side opening in the rear of the cavity.

Part Four: GPS Antenna

The GPS antenna is required for proper operation of Apple CarPlay and Android Auto, in addition to the optional GPS if installed. The GPS antenna is included in the ix212 hardware.




Step 1

Position the **GPS Antenna** and route the antenna cable down into the glove box area. Replace the A pillar panel and ensure the cable does not interfere or get pinched.



Step 2

Continue routing the GPS cable across the inner dash towards the radio opening securing with zip ties.



Step 3

Route the GPS cable into the CD/DVD area through the right side opening at the rear of the cavity.

Stinger ix212 HORIZON12

SRX-GM14128

Radio Replacement Kit for select
2014-2019 Silverado/Sierra Trucks


Section 3: Interface and Main Harness Connections and Preparation

Part One: RP5-GM51 Radio Interface Connections



Step 1

From the **Main Harness (SRK-GM14HX-HAR)**, connect the “Power” (1), “Vehicle Harness” (2) and “Radio Harness” (3) connections to the GM6A-SRK module




Step 2

For the speaker output connection, select “**Amplified**” if your vehicle is equipped with a factory BOSE system or aftermarket amplifiers. Select “**Non-Amplified**” if it is not equipped with BOSE and running the factory audio system.




Step 3

Connect the 10 Pin **PAC Link Cable (10P-2-10P-6-HAR)** to the “Expansion Port.”



Step 4

Connect the 2 pin, 8 pin and 14 pin connectors from the **Main Harness Adapter (SR-SRK-ADAPT-IX2XX)** to the **Main Harness (SRK-GM14HX-HAR)**.



Step 5

Connect the other end of the 10 pin **PAC Link Cable** to the **PAC Link Module (PL1)**. From the **Main Harness Adapter (SR-SRK-ADAPT-IX2XX)** connect the 3 pin connector labeled “PAC Link (PL1)” to the **PAC Link Module**.



Step 6

Bundle any excess wire and zip tie the **PAC Link Module** to the **Main Harness**.


Stinger ix212 HORIZON12

SRX-GM14128

Radio Replacement Kit for select
2014-2019 Silverado/Sierra Trucks

Section 3: Interface and Main Harness Connections and Preparation (Continued)


Part Two: Main Harness Connections (SR-GM14H-HAR-A) (Continued)



Step 5


Connect the **Differential Video Adapter (RPA-VA1)** to the 6-pin lead on the **Main Harness**.

Connect the male and female ends of the Light Green leads together.



Step 6

Connect the "AUX Audio" RCAs from the **Main Harness** to the "AUX IN" RCAs on the ix212's **16 Pin AV Harness**.



Step 7

Connect the "REVERSE CAM" RCA from the **Main Harness** to the "REVERSE CAMERA IN" RCA on the **16 Pin AV Harness**.


Section 4: Display Mounting Panel Preparation

Part One: Transferring the Climate Controls



Step 1

With the factory radio display / climate control panel face down, apply slight pressure to the front of the controls while releasing the locking tabs around the perimeter.



Step 2

Once all the clips are released, remove the climate controls from the factory bezel.



Step 3

Align the controls in the **Display Trim Panel** and push to seat and lock all the retaining clips.

Stinger ix212 HORIZON12

SRX-GM14128

Radio Replacement Kit for select
2014-2019 Silverado/Sierra Trucks

Section 5: Radio Module Preparation

Part One: Radio Module Side Brackets



Step 1

Locate the two **Side Mounting Brackets** and four M5x10 screws.



Step 2

Using two M5x10 screws attach one side bracket as shown above.



Step 3

Using two M5x10 screws attach the other side bracket as shown above.

Section 6: Radio Unit Installation

Part One: Mounting the Radio Module



Step 1

Slide the ix212 **Radio Module** into the factory radio opening. You may need to push the retaining clip up to slide the radio all the way in.



Step 2

Once the bracket tabs contact the sub dash, secure with supplied #8 x 1/2" screws.


Stinger ix212 HORIZON12

SRX-GM14128

Radio Replacement Kit for select
2014-2019 Silverado/Sierra Trucks

Section 6: Radio Unit Installation (Continued)

Part Two: In-Vehicle Harness and Cabling Connections



Step 1A

IO3, IO4, IO5, IO6: Connect the Green and Gray **Main Harness (SRK-GM14HX-HAR)** (1) connectors to the matching plugs in the vehicle.

IO4, IO5, IO6: If equipped, connect the Yellow RCA from the **CAM-GM51-HAR** to the "CAM-GM51 INPUT" (2) and connect the wire from the **GM5LIN-SW-HAR** to the "SWC INPUT" (3).



Step 1B

IO5 or IO6:
Connect the 8 pin gray connector from the **Main Harness** to the matching 8 pin gray connector in the vehicle that was removed from the OEM radio.



Step 1C

IOB:
Connect the Mustard and Gray **GM52-ADAPT** connectors to the matching plugs in the vehicle. Connect the other end to the **Main Harness**.




Step 2

2018-19 IOB Only:
Plug the 20 pin harness that was removed from the factory display into the **GM5CAM-DIS-HAR**.



Step 3

Connect the **AM/FM Antenna Adapter (BAA22)** to the black factory antenna cable. Plug the other end of the **BAA22** into the "ANT" port on the **Radio Module**.



Step 4

Connect the **GPS Antenna** (1) and the two USB cables (2) to the **Radio Module**. The USB-C will handle Apple CarPlay and Android Auto

Stinger ix212 HORIZON12

SRX-GM14128

Radio Replacement Kit for select
2014-2019 Silverado/Sierra Trucks


Section 6: Radio Unit Installation (Continued)

Part Two: In-Vehicle Harness and Cabling Connections (Continued)



Step 5

From the **SR-SRK-ADAPT-IX2XX** harness, connect the "26 PIN RADIO" (3) connector to the "POWER" port on the **Radio Module**.




Step 6

Connect the **16 Pin A/V Harness** (4) and **Data Harness** (5) to the "AV IN" port on the **Radio Module**.



Step 7

Use the supplied two-sided tape to secure the **Radio Replacement Interface** in the lower CD/DVD cavity.



Step 8

If using the **External Speaker**, connect the **External Speaker** to **SRK-GM14HX-HAR**.

These are the connections for a typical installation. If adding additional cameras, amplifiers or satellite radio, those connections should be made at this point.



Step 9

While holding the **Display Mounting Panel**, connect the **Display Cable** to the **Radio Module**.

Stinger ix212 HORIZON12

SRX-GM14128

Radio Replacement Kit for select
2014-2019 Silverado/Sierra Trucks

Section 6: Radio Unit Installation (Continued)

Part Two: In-Vehicle Harness and Cabling Connections (Continued)



Step 10

Run **External Mic** connection and 4 pin **Data plug** through the left cut out of the **Display Mounting Panel**.



Step 11

Run factory **AC connector** through right cut out of the **Display Mounting Panel** and place panel in position.



Step 12

Reinstall 7mm screws to **Display Mounting Panel**.



Step 13

Connect **Volume Knob** connector to the **Data** connector and plug the external mic to 3.5 external mic connector.



Step 14

Reconnect the HVAC controls.



Step 15

Place the **Main Frame Assembly** in place and run through a full functionality test. Do not snap in **Main Frame Assembly** until after a functionality test has been complete.

Before complete reassembly, it is recommended to start the vehicle and check the chime volume and all other functionality...

Volume, Balance, Fade
AM/FM Reception
USB
Android Auto
AC Controls

Steering Wheel Controls
Bluetooth
Apple Carplay
Camera(s)
Vehicle Info

Stinger ix212 HORIZON12

SRX-GM14128

Radio Replacement Kit for select
2014-2019 Silverado/Sierra Trucks

Product Updates (Firmware)

Firmware Updates (RadioPRO)

The PAC GM6A-SRK interface can be updated with new firmware as it becomes available. Please visit www.PAC-audio.com/firmware for available updates and select SRX-GM14128.

Firmware Updates (Stinger Radio and PAC Application APK)

To update the ix212 radio firmware, refer to:

<https://stingersolutions.com>

RadioPRO LED Feedback

LED 1:

Blinks Red - Interface is configuring
Solid Red - Accessory power is on
Flashes Green - SWC button pressed
Blinking Green - SWC remap
Off - Accessory power is off

LED 2:

Solid Green - Interface is running
Blinking Amber - Connected to USB
Off - Interface is sleeping

LED 1 & 2:

Alternating Blinking Amber - Interface is entering sleep
Alternating Blinking Red - Master reset

Technical Support

Email: support@StingerSolutions.com

Phone: 727-592-5991