

# Ideal BarTap®

High Flow (HF) or Eco Flow (EF)

IBT-D-PSS-HF  
IBT-D-PSS-EF

IBT-D-MSS-HF  
IBT-D-MSS-EF

IBT-D-GSS-HF  
IBT-D-GSS-EF

IBT-D-BSS-HF  
IBT-D-BSS-EF

IBT-D-YSS-HF  
IBT-D-YSS-EF

IBT-D-ZSS-HF  
IBT-D-ZSS-EF



Polished  
Stainless Steel



Matte  
Stainless Steel



PVD Gun Metal Gray™  
Stainless Steel



PVD Satin Black  
Stainless Steel



PVD Brushed Gold  
Stainless Steel



PVD Burnished Bronze  
Stainless Steel

## Specifications

- Single-lever control
- Ceramic disk cartridge
- Forward rotating COMFORTFEEL™ lever handle
- Q-Dock™ docking system holds hand spray in place
- Ergonomic slide switch to select Ideal Flow, Laminar or Spray Flow
- Automatic return to laminar flow
- Concealed easy clean spray face
- Spout rotates 360°
- Counterweight
- Dual check valves
- 24" stainless steel flexible hoses 3/8" compression
- Maximum counter thickness 2"
- Minimum install hole diameter 1 3/8"
- Optional base ring included
- Total height 15 13/16"
- High Flow 2.2 GPM maximum flow rate
- Eco Flow 1.8 GPM maximum flow rate
- For use with Water Filtration System\* (not included)

\*Note: May reduce water flow

## Construction

- Solid 316L machined stainless steel construction
- Available in Polished, Matte, PVD Gun Metal Gray™, PVD Satin Black, PVD Brushed Gold, PVD Burnished Bronze
- Indoor & outdoor
- Limited Lifetime Warranty
- Made in Italy

## Codes/Standards

- ASME 112.18.1
- CSA B125.1
- NSF 61, 372
- CALGreen
- cUPC™
- ADA

