

BUTTON REMAPPING GUIDE

BUTTON REMAPPING FOR STEERING WHEEL CONTROL INTERFACES

1. Set any of the six dipswitches to ON. (All OFF is reserved for SW update).

2. Connect the USB-C cable to your PC, Mac, or smartphone, then connect it to the interface.

3. The interface will show up as a drive on the connected device and will be identified by the name "INTERFACE".

4. Double click the drive to open it.

5. You will find a .txt file named "Interface Configuration." Open it.

6. By default, this configuration file is blank and does not contain any steering wheel control re-mapping:

7. Editing and saving this text file onto the interface allows us to change the functions of the buttons during normal operation.

8. Before you begin to edit the Configuration File, take a copy of the blank file so that you can always revert back to the original system.

9. The following steering wheel buttons can be re-configured or given two functions. The buttons available to you will depend on which car the interface is being fitted to. The following list shows all possible buttons on all possible cars:

VOL_UP	PRESET_UP	OFF_HOOK
VOL_DOWN	PRESET_DOWN	ON_HOOK
TRACK_UP	SOURCE	PHONE
TRACK_DOWN	ATTENUATE	VOICE_REC

The aftermarket radio control commands that can be assigned to them are shown below.

Please note, not all functions are supported by all aftermarket radios

VOL_UP	PRESET_UP	OFF_HOOK
VOL_DOWN	PRESET_DOWN	ON_HOOK
TRACK_UP	SOURCE	VOICE_REC
TRACK_DOWN	ATTENUATE	

In addition to button re-mapping, we can add a dual function to each button on the steering wheel. Each button can have a short press command and a long press command assigned to it.

The length of time in milliseconds that the button needs to be held for is considered a long press can also be configured.

Example

Here is an example of configuring the source button so that a short press performs the source function, while a long press activates voice recognition. In this example, we will set the long press hold time to 1 second (1000 milliseconds).

First, place the steering wheel button you want to configure inside square brackets:


[SOURCE]

Next, the text that follows will configure the actions for that button. It is crucial to maintain the exact text for button names and actions as shown above, and to follow the syntax precisely as illustrated in the example below:

[SOURCE]
SHORT=SOURCE
LONG=VOICE_REC
HOLD_TIME=1000

You can repeat this process multiple times for each button you want to remap. Note that it is not necessary to write a remap configuration for any button whose standard function you wish to keep unchanged. Finally, remember that you can only configure the steering wheel buttons that are available on your steering wheel.

10. Make sure you save the new edited Configuration File back onto the INTERFACE.



Devices and drives

Local Disk (C:) 844 GB free of 930 GB

(INTERFACE) (E:) 0 bytes free of 8.00 KB FAT

This PC > (INTERFACE) (E:)

Name	Date modified	Type	Size
Interface Configuration	...	Text Document	1 KB

Interface Configuration

```
File Edit View
;
; /////////////////////////////////////////////////// BLANK CONFIG FILE ///////////////////////////////////////////////////
;
;
```

Here is an example of a completed configuration file:

Interface Configuration

```
File Edit View

[SOURCE]
SHORT=SOURCE
LONG=OFF_HOOK
HOLD_TIME=1500

[VOL_UP]
SHORT=VOL_UP
LONG=ON_HOOK
HOLD_TIME=1500

[VOL_DOWN]
SHORT=VOL_DOWN
LONG=VOICE_REC
HOLD_TIME=1500
```