


# Designer Pyramid Wall Mount Hood with Offset Lip, Magic Lung® Blower

A crisp pyramid silhouette and distinctive offset lip give this hood a timeless architectural look. Patented Magic Lung® technology delivers powerful yet exceptionally quiet ventilation through centrifugal filtration, while SensaSource® automatically adjusts blower speed for enhanced grease control and fire safety. Dishwasher-safe components simplify cleanup. Matching duct covers sold separately.


To view available finishes & accessories please visit [ventahood.com/products/JPH354/C2](http://ventahood.com/products/JPH354/C2)

## SPECIFICATIONS

|                                           |                            |
|-------------------------------------------|----------------------------|
| WIDTH                                     | 54"                        |
| DEPTH                                     | 24"                        |
| HEIGHT                                    | 30"                        |
| CFM <sup>1</sup>                          | 900                        |
| EQUIVALENT CFM <sup>2</sup>               | 1350                       |
| SOUND RATING<br>(HIGH SPEED) <sup>3</sup> | 6.3 Sones / 56.8 dB        |
| LIGHTING <sup>4</sup>                     | 4 LEDs<br>2700K Warm White |




## DUCT COVERS




Wall Mount Duct Cover  
Models: WDCRND-\*

## RECOMMENDED MOUNTING HEIGHT




NOTE: Exceeding recommended mounting height may compromise performance.


## CONNECTIONS




900 CFM B200 Dual & B100 Single Blower (Top View)



(Front View)



VP562 Transition (Optional) For  
B300 (B200 Dual Blower & B100  
Single Blower)



VP562 transition centers outlet over  
top of hood.

## ELECTRICAL/MECHANICAL SPECIFICATIONS FOR BLOWER UNIT

| MODEL                          | VOLTS | AMPS | HZ | RPM  | CFM<br>@ 0.0" SP <sup>5</sup> | CFM<br>@ 0.1" SP | CFM<br>@ 0.2" SP | CFM<br>@ 0.3" SP | MIN. ROUND<br>DUCT SIZE |
|--------------------------------|-------|------|----|------|-------------------------------|------------------|------------------|------------------|-------------------------|
| B200 Dual & 1 x<br>B100 Single | 115   | 6.0  | 60 | 1550 | 900                           | 804              | 725              | 655              | 10" (79sq.in.)          |

<sup>1</sup> CFM (cubic feet per minute) measures airflow. <sup>2</sup> Because Magic Lung® blowers use centrifugal filtration instead of traditional baffle or mesh filters, they move air more efficiently. When comparing to other brands, use Equivalent CFM to understand real-world performance. <sup>3</sup> Sones measure perceived loudness—lower values indicate quieter operation. Decibel values shown are approximate equivalents. <sup>4</sup> This model is not available with heat lamps. <sup>5</sup> Airflow (CFM) decreases as duct resistance (static pressure) increases. Values at 0.1"–0.3" SP reflect typical installed conditions.