

606 Series

6-Year Tank & Parts Warranty

	MODEL NUMBER	GAL. CAP.	1st HR. RATING GALS.	ENERGY FACTOR	NATURAL		PROPANE		HEIGHT WITH DIVERTER	DIAMETER
					INPUT PER HR.	RECOVERY 90° RISE	INPUT PER HR.	RECOVERY 90° RISE		
TALL	6 30 YORT	30	58	.61	32,000	33	35,500	31	61	16
	6 40 GORT	40	68	.59	35,500	36	35,500	36	61-3/4	18-1/2
	6 50 GORT	50	83	.59	35,500	36	35,500	36	61	20
HO	6 100 XRRT*	100	N/A	N/A	75,100	81	75,100	81	72	26-1/2
SHORT	6 30 YJRS**	30	54	.61	30,000	30	29,000	29	49	18
	6 40 GORS	40	67	.59	35,500	36	36,000	37	51-3/8	20
	HO 6 75 XRRS*	74	N/A	N/A	75,100	81	75,100	81	61	26-1/2
UTILITY MODELS	HO 6 40 GOCT†	40	70	.62	40,000	41	36,000	37	61-3/4	20-1/2
	HO 6 50 GOCT†	50	88	.62	40,000	41	37,000	37	60-7/8	22
MOBILE HOME†	6 30 YJMT**	30	69	.61	30,000	30	29,000	29	59-3/4	16
	6 40 YJMT**	40	69	.59	40,000	40	36,000	36	62	18
	DV 6 30 NHDST 2*	30	54	.61	30,000	31	30,000	31	56	18
	DV 6 40 NHDST 2*	40	64	.59	32,000	33	32,000	33	56-1/2	20

Model numbers shown indicate Natural Gas as fuel source.

For Propane Gas, change "Y" to "H", "X" to "C" or "G" to "L" in model numbers (examples: 6 30 HORT 4 & 6 75 CRRS & 6 50 LORT).

Mobile Home models are convertible from natural gas to LP (Propane) operation.

†Reliance 606 Series Utility Models qualify for most Utility Rebate Programs.

*Indicates not FVIR Compliant Gas Water Heaters

**For installation at elevations over 5,000' to 7,000' above sea level, add "D" to the model number (example: 6 30 YJRS D).

HE=High Efficiency HO=High Input/Output DV=Direct Vent (must order Roof Jack kit with each water heater).

Recovery values shown are rounded to nearest gallon and at a 90°F temperature rise.

Dimensions shown for height and diameter are in inches.

Reliance® Water Heater Company reserves the right to make product changes or improvements without prior notice.

