



Compact Programmable®



• CP12E10 Profile

- 11800 BTU Cooling
- 10.8 EER
- 10.1 Cooling Amps
- Moisture removal - 3 pints/hour
- Net weight - 100 lbs.
- Energy Star® qualified
- 115 Volts
- 1111 Cooling Watts
- Room Air Circulation 310 CFM
- Circuit Breaker Rating: 125V-15A

Compact Programmable® Models

Other Models


- CP06E10
- CP08E10
- CP10E10
- CP14E10
- CP18E30
- CP24E30
- CP05N10

Compact Programmable Features

- Deluxe cooling line for home or light commercial use
- Remote control convenience
- Window or wall installation (Except CP05)
- EERs up to 10.8
- Includes installation hardware
- Expandable side curtains reduce outside noise and light
- 4 air flow directions
- Auto swing louvers
- Power cord runs left or right for more installation options
- Stale air exhaust
- Washable anti-microbial air filter

Chassis Dimensions

Height	Width	Depth with Front	Depth (Hood to Louvers)	Minimum Extension into Room	Minimum Extension Outside	Window Width		Thru-the-Wall Finished Hole	
						Min.	Max.	Height	Width
15"	23 5/8"	22 1/8"	8 3/4"	4 1/2"	12"	27"	39"	15.25"	23.825"



Plug face:
NEMA # 5-15P

Installation Notes

- Supply Cord - All with right angle plug 6' on 115V models; 4' on all 230/208V.
- Room air conditioners include accessories for window or thru-the-wall installation.
- TWINTEMP® models include accessories for thru-the-wall installation only. Window mounting requires use of optional accessory kit as listed below:
 - **WIKQ**: EQ08L11
 - **WIKS**: ES12L33, ES16L33, YS09L10, YS13L33
 - **WIKM**: EM18L34, EM24L35, YM18L34
 - **WIKL**: EL36L35, YL24L35