

# CHORUS 705 V

## Product specification sheet

Compact loudspeaker,  
wall mounting supplied.  
Can be used as an effect speaker.

5" (140mm) Polyglass midbass.  
Dynamic midrange,  
fast and tight bass.

Aerodynamic port.  
Low distortion.



Aluminum/Magnesium inverted  
dome TNV tweeter.  
Extended response to 28kHz.

Solid MDF construction  
up to 1" (25mm) width.  
Non parallel inner wall structure.

OPC crossover. Perfect staging.  
New insulated Focal terminals.

> Chorus 705 V, Light Walnut finish.




- ♦ Speakers designed and manufactured by Focal.
- ♦ Exceptional sound and quality for the price.
- ♦ Light Walnut, Wengé, Black Ash finishes.

Other finishes available



Wengé



Black Ash



Optional 24" (60cm) S 700 V stand.

Type	2-way bass reflex bookshelf loudspeaker
Drivers	5" (140mm) Polyglass midbass 1" (25mm) TNV Al/Mg inverted dome tweeter
Frequency response (+/- 3dB)	65Hz - 28kHz
Low frequency point (- 6dB)	57Hz
Sensitivity (2.83V/1m)	89dB
Nom. impedance	8 Ohms
Minimum impedance	3 Ohms
Recommended amplifier power	25 - 100W
Crossover frequency	3000Hz
Dimensions (HxWxD)	12 <sup>3/8</sup> x 7 <sup>9/16</sup> x 9 <sup>3/4</sup> " (315 x 192 x 248mm)
Net weight	12.5lb (5.7kg)

*Chorus 705 V is the ideal loudspeaker for installation in rooms of modest dimensions (approximately 15 m<sup>2</sup>). With a responsive and lively bass, it represents the foundations of a great system, especially when paired with the SW 700 V subwoofer. Can also be used as an effect speaker.*

