

- 60W x 4 RMS (20Hz-20kHz, < 1% THD+N, 4 Ohms, 14.4V)¹
- This unit has a maximum output power of 110W per channel at 4 Ohm.
- 70W x 4 RMS (20Hz-20kHz, < 1% THD+N, 2 Ohms, 14.4V)
- This unit has a maximum output power of 150W per channel at 2 Ohm.
- Conformal Circuit Board Coating
UV-resistant paint
Anti-rust paint on front panel and bottom plate
Gold-plated Screws, Terminals, and Connections
- High Level Input with Sensing Power On
- 80Hz low pass filter switch
- 80Hz high pass filter switch
- CEA-2006 Power Compliant



1. CEA-2006 Compliant – Standardized “Voluntary” Testing & Measurement Methods for Mobile Audio Amplifiers. This standard advocates a uniform method for determining an amplifier’s RMS power and signal-to-noise ratio. Using 14.4 volts, RMS watts are measured into a 4-ohm impedance load at 1 percent Total Harmonic Distortion (THD) plus noise, at a frequency range (for general purpose amplifiers) of 20 Hz to 20,000 Hz.

© 2009 Sony Electronics Inc. All rights reserved. Reproduction in whole or in part without written permission is prohibited. Sony, Memory Stick, nav-u, Quick-BrowZer, Walkman, Xplod, ZAPPIN, and the Sony, nav-u and Xplod logos are trademarks of Sony. iPhone and iPod are trademarks of Apple Inc., registered in the U.S. and other countries. Bluetooth is a trademark of Bluetooth SIG, Inc. NAVTEQ Maps & Traffic is a trademark of NAVTEQ. All other trademarks are trademarks of their respective owners. Features and specifications are subject to change without notice. Non-metric weights and measures are approximate.

Last Updated: 09/01/2010