

Specifications

Technical:

- » **Inputs:** KD-CATHDTX - 1 HDMI connector. KD-CATHDRX - 2 CAT5 IN on RJ45 connectors
- » **Outputs:** KD-CATHDTX - 2 CAT5 OUT on RJ45 connectors. KD-CATHDRX - 1 HDMI connector
- » **Bandwidth:** 10.2 Gb/s TMDS bandwidth
- » **EQ Adjustments:** Auto Adjust
- » **HDMI® and HDCP Licensing:** Fully licensed and compatible with all HDMI and HDCP technologies
- » **Link and Range:** Single Link: (1080p/60) 12 bit color depth, 1920x1200 max. UTP 140 ft., STP 150 ft.; (1080i/60, 720p, 1080p/24) UTP 280 ft., STP 300 ft.
- » **Deep Color Support:** Supports Digital Video Formats in Deep Color Mode at up to 12 bits/color
- » **Lossless Compressed Digital Audio:** Supports lossless compressed digital audio (Dolby® TrueHD, Dolby® Digital Plus and DTS™-HD Master Audio)
- » **DDC Signal (Data):** Input DDC Signal: 5 Volts p-p (TTL)
- » **HDMI Video/Audio Signal:** Input Video Signal: 1.2 Volts p-p
- » **HDMI Connector:** Type A, 19 Pin Female
- » **RJ45 Connector:** Shielded Link Connector RJ45
- » **DDC Communication:** EDID and HDCP Transparency from Display to Source
- » **Power:** External Power Supply – 5V DC / 2A, 110-240 VAC, 50-60 Hz

General

- » **Regulation:** CE, RoHS, WEEE
- » **Enclosure:** Black Metal
- » **Product Dimensions:** L = 3.5" W = 1.75" H = 1"
- » **Shipping Carton Dimensions:** L = 7.5" W = 8.5" H = 2"
- » **Product Weight:** 1 lb
- » **Shipping Weight:** 2 lbs
- » **Accessories:** Mounting Bracket, Locking HDMI Cable Clip, UL Certified Power Supplies