

D5654XXLHS/TH Tubular handle

Turbo Drying

Capacity (max): 17 Place settings

Upper basket type: Exclusive height adjustable

Bowls and cutlery

Lower basket type: Exclusive lower basket

Programs

Heavy wash

Normal programme

Time program

Delicate wash

Quick wash

Super quick Eco wash

Upper half / Lower half

opper riair / Lower ria

Rinse & Dry

Rinse and hold

Sanitation wash

Options

Delayed start: 24 h High temperature Long dry

Cleaning systems

Number of spray zones: 9 Self cleaning filters AquaLevel™ Sensor

Drying system

Turbo Drying™

Features

8 stainless steel parts Fault indication

Interior light Salt indication

Rinse-aid indication

Time remaining indicator

Voice signal for the end of washing cycle

Safety

AquaSafe™

SteamSafe™

 $KidLock^{TM}$ - lock the door

Baskets

Upper basket type: Exclusive height adjustable Lower basket type: Exclusive lower basket

Bowls and cutlery



General

Size: XXL

Mode of installation: Built-in Display type: LED display Number of programs: 12 Noise level: 46 dB(A) Number of baskets: 3

Max loading height upper basket: 9 1/16 (230 mm) Max loading height lower basket: 11 7/16 (290 mm)

Capacity (max): 17 Place settings EAN code: 3838942647284

Dimensions and installation

Height: 34 3/8 (873 mm) Width: 24 (610 mm) Depth: 22 7/8 (581 mm)

Packaging height: 37 3/8 (950 mm)
Packaging width: 25 3/16 (640 mm)
Packaging depth: 26 3/4 (680 mm)
Length inlet hose: 66 1/8 (1680 mm)
Length outlet hose: 41 3/4 (1060 mm)
Cord length: 46 7/16 (1180 mm)
Adjustable front legs: Adjustable front legs

Weight net: 110 lbs Weight gross: 115 lbs

Technical information

Connection rating: 1300 W

Current: 15 A Voltage: 120 V

Consumption

Estimated yearly energy consumption: 218 kWh Energy consumption/cycle: 1,01 kWh



D5654XXLHS/TH Tubular handle

XXL DISHWASHERS


UNIT DIMENSIONS


	U.S.	Metric
Height (Adjustable)*	34-3/8" to 36-1/2"	873 mm to 927 mm
Width	24"	610 mm
Depth (Includes high loop)	22-7/8"	581 mm
Depth w/Handle	24-7/8"	632 mm
Depth w/Door Open	49-1/2"	1257 mm
Weight	110 lb	50 kg


TECHNICAL DATA

Electricity	120V, 60Hz, 15 amp
Water pressure	4.2 - 140 psi,
	0.03-1.0 MPa,
	0.3-10 Bar
Heating element	1200 watt
Max loading	1300 watt

* Total height can be reduced by 1/2" (13 mm) by removing upper trim, and lowering side trim (2).







PREPARING THE LOCATION

PREPARING THE LOCATION


	U.S.	Metric
Height*	34-3/8" to 36-1/2"	873 to 927 mm
Width	24"	610 mm
Depth	24"	610 mm

The best place for your dishwasher is in the kitchen near the sink. This makes it easier to connect the water and drain supply lines.

A built-in dishwasher must be enclosed on the top, both sides and the back.

The power-supply receptacle for the appliance shall be installed in a cabinet or on a wall adjacent to the undercounter space in which the appliance is to be installed.

The electrical and water supplies should enter through the area indicated by the shading on the illustration at right. Preferably, they should come through the right side of the machine. The access hole must be round and smooth and no bigger than 1-1/2" (38 mm) in diameter. If the partition is metal, it needs to be covered with an edge protector. Use caution when the appliance is installed or removed, to reduce the likelihood of damage to the power-supply cord.



^{*} Total height can be reduced by 1/2" (13 mm) by removing upper trim, and lowering side trim (2).