

Say goodbye to your drying worries.

The Maytag® Neptune® Drying Center



to free me from the laundry."

You're not the kind of person who throws laundry in the dryer and considers it done. You flat-dry your daughter's favorite sweater so it won't shrink. You hang-dry pants and T-shirts so you have less ironing to do. All these extra steps keep your family's clothes looking their best — but keep you tied to the laundry room. Until now.

Introducing the new Maytag® Neptune® Drying Center. Now you can say goodbye to your drying worries.





"I can load it and leave it — and not worry about shrinking her favorite clothes."



Two-in-one dryer does it all.

You get a tumble dryer as well as the new upper drying cabinet featuring a revolutionary gentle drying system that helps reduce shrinkage and damage.



Prevents shrinkage.

New drying technology helps eliminate the unavoidable shrinkage that occurs from tumble-drying. So after drying, your favorite clothes still fit.



Dries clothes in a few hours — not days.

The drying cabinet dries faster than air-drying, so you don't have to plan ahead to wear that special sweater.



Removes odors.

Steam and optimum temperatures work together to grab smoke or food odors, while gentle airflow removes them.



Your days of babysitting the laundry are over. The Maytag® Neptune® Drying Center is the perfect place to dry and care for all your clothes.



With five removable mesh shelves, special ShapeSaver™ hangers and door hooks, you can customize the interior space to fit your needs.

"Leave it to Maytag to make a dryer that helps organize my life."



Reduces wrinkles.

Steam, airflow and wrinkle-release motion help reduce wrinkles from clothes hung in the drying cabinet.



Hides the mess.

The upper drying cabinet holds up to 13 items at once. With a place for everything — including hooks for hats — the mess stays out of sight.



Adds a fresh, clean scent.

It's easy to add fragrance to any cycle in the tumble dryer or upper drying cabinet — just use your favorite dryer sheet.



Saves you money too.

You can freshen your "dry clean only" clothes at home — saving money and trips to the dry cleaner.

The dryer you've always wanted is here.

The Maytag[®] Neptune[®] Drying Center

BreezeCare™ Drying System

Air circulates around and through every item in the cabinet, using gentle temperatures that are easy on fabrics.

Removable Mesh Shelves

Use all five shelves at once — or remove them and store them neatly on the side of the cabinet until you need them.



Largest Capacity With 24.3 Cu. Ft. Of Total Space

The 7.0 cu. ft. tumble dryer dries clothes using traditional tumble action, while the 17.3 cu. ft. drying cabinet air-dries, flat-dries or refreshes special items.



WrinkleRelease™ Rod

Gentle motion waves clothes through soft breezes, helping reduce wrinkles from hanging clothes.



The Drying Center comes with ShapeSaver™ hangers that help eliminate bumps caused by traditional hangers in the shoulders of shirts.



Fragrance/Humidity Center

Add fragrance to any cycle by using your favorite dryer sheet in the Dryer Sheet Caddy. For humidity, just fill the water bottle with regular tap water.



Maytag®-Exclusive Features

DuraCushion™ dryer drum; seamless, one-piece upper cabinet liner; heavy-duty front and rear suspension; and powerful motor are designed for years of reliable performance.

You can depend on the Maytag[®] Neptune[®] Drying Center.



Leading The Way In Laundry

The Maytag® Neptune® brand represents our very best. These super-premium products offer industry-changing breakthroughs in technology that help solve the laundry challenges faced by our most demanding customers.

Maytag® Neptune® Drying Center Warranty

10 Years Free parts on replacement of dryer drum and exterior cabinet rust-through.

5 Years Free parts on replacement of LED controls and WrinkleRelease[™] rod.

2 Years Free parts (excluding ShapeSaver™ hangers).

1 Year Free parts and labor.

PRIORITY ONE.

As the owner of a Maytag® Neptune® Drying Center, you are entitled to an unprecedented level of after-sale support. This unique program offers dedicated toll-free assistance. Plus, priority service scheduling should any in-home calls be required. Call toll-free 1-888-4-MAYTAG.

See warranty for complete details.

See your Maytag® Neptune® dealer today for more information, or visit www.maytag.com.



Maytag® Neptune® Drying Center Features And Specifications

Available in electric or gas. Electric model requires a 240-volt, 30-amp hookup; gas model requires a 120-volt, 20-amp hookup. Dimensions for both models are $33\,^{1}\!/^{2}$ " (85.1 cm) W x 74" (188.0 cm) H x 29" (73.7 cm) D.

Model	MCE/G8000
Upper Drying Cabinet Features	
Capacity — cu. ft.	17.3
Controls	LED
BreezeCare™ Drying System	•
Dry Clothes Cycle	•
Refresh Cycle	•
Low Temperature	•
Extra-Low Temperature	•
Wrinkle Release Option	•
Remove Odor Option	•
Add Fragrance Option	•
Time Remaining Indicator	•
Cycle Status Indicator	•
Adjustable Time	•
WrinkleRelease™ Rod	•
Removable Mesh Shelves	5
ShapeSaver™ Hangers	3 [†]
Accessory Door Hooks	4
Dryer Sheet Caddy	•
Water Bottle	•
Interior Cabinet Light	•
Shelf Storage Hanger	•
End-Of-Cycle Signal	Adjustable
Tumble Dryer Features	
Capacity — cu. ft.	7.0
Controls	LED
GentleBreeze™ Drying System	•
IntelliDry® Dryness Control	•
Temperature Settings	4
Sensor Dry Cycle	•
Time Dry Cycle	•
Air Fluff Cycle	•
Wrinkle Release Cycle	•
Wrinkle Prevent Option	•
Damp Dry Signal	•
Time Remaining Indicator	•
Cycle Status Indicator	•
End-Of-Cycle Signal	Adjustable
Reversible Door	·
High-Capacity Blower	•
Drum Light	•
DuraCushion™ Dryer Drum	•
Electric Dryer Venting Directions	2
Gas Dryer Venting Directions	2
Sound-Silencing System	EQ™ Plus
Country Cyclotti	LQ IIU0

Dimensions for electric and gas models.

Overall Dimensions	in. (cm)
Width	33 1/2 (85.1)
Height	74 (188.0)
Depth	29 (73.7)

DRYER CONTROLS: Electronic LED.

UPPER MOTOR: 65W, 120-volt, 60 Hz, single-phase, thermoprotected against overload, automatic reset.

LOWER MOTOR: 245W, 120-volt, 60 Hz, single-phase, thermoprotected against overload, automatic reset.

UPPER CABINET AIRFLOW: 80 cubic feet (2.3 cu. m) per minute.

TUMBLE DRYER AIRFLOW: 175 cubic feet (6.2 cu. m) per minute.

EXHAUST: Use a minimum of 4" (10.2 cm) diameter rigid aluminum or qalvanized-steel duct. Never use plastic, nonmetal or combustible duct.

UPPER HEATING ELEMENT (Both Models): Tubular heater, 1,200W, 10A.

TUMBLE DRYER HEATING ELEMENT (MCE Model): Open coil; 4,800W, 21A when using tumbler only; 3,300W, 14A when using tumbler and upper cabinet.

SINGLE-PORT BURNER (MCG Model): Automatic electric burner with automatic ignition.

AUTOMATIC PRESSURE REGULATOR (MCG Model): Self-adjusting valve automatically compensates for variation in gas pressure.

ELECTRICAL RATING (MCE Model): 240-volt, AC, 60 Hz, draws approximately 5,100W overall.

ELECTRICAL RATING (MCG Model): 120-volt, AC, 60 Hz, draws approximately 1,700W overall.

GAS RATING (MCG Model): 18,000 BTU/hr. for tumble dryer.

FUSE REQUIREMENTS:

MCE model: 30A. MCG model: 20A.


LEVELING LEGS: Adjustable to level unit for proper installation.

WEIGHTS (Crated/Uncrated): 273 lbs. (124 kg)/241 lbs. (109 kg).

Available in White or Bisque.

Maytag® Neptune® Drying Center Installation

The Maytag® Neptune® Drying Center is not a built-in unit, so it doesn't require extra cabinetry. It's only about 6" wider than a traditional dryer.



Duct vent is 13 ½" (34.3 cm) from left side of machine, 4" (10.2 cm) from bottom of machine. Gas pipe is 8 7/8" (22.5 cm) from left side of machine, 3" (7.6 cm) from bottom of machine. Power cord is 20 ½" (52.1 cm) from left side of machine, 25½" (64.8 cm) from bottom of machine.



The Drying Center gas model is designed to operate on a 120-volt/20-amp circuit, using an electrical plug and outlet similar to those shown. If your laundry room doesn't have this type of outlet, contact an electrician who can install a proper outlet designed to carry the necessary amperage. The laundry outlet must be less than 6 feet from the washer/gas dryer.

NOTE: Two people are required for proper installation of the Maytag® Neptune® Drying Center. Minimum installation opening: 38 ¹/₂" (97.8 cm) W x 76" (193.0 cm) H x 30 ¹/₂" (77.5 cm) D.

Installation Requirements:

- Grounded electrical outlet. (20-amp circuit is required for gas model.)
- 240-volt, 30-amp power cord for electric model. (Power cord is supplied on gas model.)
- Gas line for gas model.
- Rigid metal exhaust ducting.

Installation Steps:

- 1. Remove unit from crate and pry off shipping base.
- If installing unit next to a washer, remove washer temporarily to allow for more access to gas line, electrical outlet, venting hookup and leveling legs.
- 3. MCE model:
- a. Install 240-volt, 30-amp power cord. (Not included.)
- b. Attach venting duct.
- 4. MCG model:
- a. Attach gas supply.
- b. Attach venting duct.
- 5. Plug power cord into electrical outlet.
- 6. Move unit into final position.
- 7. Adjust and lock leveling legs.
- **8.** Remove all shipping material from tumbler drum and upper cabinet interior.

NOTE: Be sure to check bottom dress box for any additional debris.



[†]Accessory kit model MAL3000AXX also available.



