



#### Color Variants

RC472701  
with temperature controlled drawer  
Fully integrated appliance

#### Included accessories

#### Required installation accessories

RA460000  
Installation kit for side-by-side  
installation (for connecting any two  
columns)  
RA460010  
Additional side heating element

#### Installation Accessories

RA421710  
Stainless steel door panel with handle  
RA421730  
Aluminium door panel with handle  
RA425110  
Long stainless steel door handle  
RA460020  
Connecting element for vertically split  
appliance fronts (for a flush front)  
RA460040  
Finger protection for extra long  
furniture fronts

RC472701  
Refrigeration column  
with temperature controlled drawer  
Fully integrated appliance  
Width 30" (76.2 cm)

Width 30" (76.2 cm)  
Stainless steel interior  
Generous LED lighting concept  
Solid aluminum door bins  
Net volume 17.2 cu.ft.  
Temperature controlled drawer (32  
°F to 37 °F)  
One motorized glass shelf,  
adjustable when fully loaded  
ENERGY STAR® qualified

#### Operation

Electronic precision temperature  
control with digital temperature display.

#### Technical features

Dynamic cool air distribution with Multi-  
Flow Air system.  
Automatic defrosting with defrost water  
evaporation.  
Activated charcoal air filter.  
Energy-saving vacation mode.  
Open-door and malfunction warning  
system.

#### Cooling compartment

Net volume 17.2 cu.ft.  
(418 liters).  
No-frost technology with fast cooling.  
Temperature adjustable from 35 °F to  
46 °F (+2 °C to +8 °C).  
4 safety glass shelves (one is  
motorized, two are manually adjustable.  
2 fully extendable drawers (low and  
high) with transparent front.  
Bright interior lighting with LED sidewall  
pillars.  
3 height adjustable door bins, one of  
which is a large gallon door bin.  
1 door bin with transparent front flap.

#### Temperature controlled drawer

Net volume 0.9 cu. ft.  
Separate automatic temperature  
control with settings for fish (32°F),  
meat (35°F) and produce (37°F).  
1 continuous, fully-extendable  
temperature controlled drawer with  
transparent front and integrated  
lighting.

#### Planning notes

Flat hinge.  
Door hinge right, reversible.  
Door opening angle of 115°, optional  
90° door stop.  
Max. door panel weight 77 lb.

#### Consumption data

Energy consumption 0.849 kwh/24 h.  
Energy consumption 309.89 kwh/year.  
Noise level 39 dB.

#### Rating

Total rating 0.180 kW.  
Total Amps: 15 A.  
120 V / 60 Hz  
Connecting cable 139 1/3" with plug.

#### Product Features

Multi-Flow Air Tower  
Yes  
SUPERCool  
Yes  
SUPERFREEZE  
No  
Carbon Air Filter  
No  
Temperature Controlled Drawer  
Yes  
Humidity Control Drawer  
Yes  
Number of Door Bins - Refrigerator  
2  
Adjustable Door Bins - Refrigerator  
No  
Tilt-Out Door Bins - Refrigerator  
Yes  
Gallon Storage Bins  
1  
Number of Shelves - Refrigerator  
4  
Door Hinge  
Right reversible  
Adjustable Shelves - Refrigerator  
3  
Number of Shelves - Freezer  
Reversible Door Hinge  
Yes  
Adjustable Shelves - Freezer  
No

#### Consumption and connection features

UPC code  
825225899921  
Color / Material housing  
Colour.Material door  
Panel ready  
Not possible  
Silence level (dBA)  
39  
Watts (W)  
180  
Current (A)  
15  
Volts (V)  
120  
Frequency (Hz)  
60  
Total annual energy consumption (kWh)  
309.9  
Energy Star® qualified  
Yes  
Approval certificates  
ETL, ETL C  
Power Cord Length  
139 1/3"  
Required cutout size (HxWxD) (in)  
84" x 30" x 24 3/4"  
Appliance Width (in)  
29 3/4"  
Height (in)  
83 3/4 "  
Depth (in)  
24"  
Capacity in 0.75l (bordeaux bottles)  
Total unit gross capacity (cu. ft.) - AHAM  
17  
Product packaging dimensions  
(HxWxD) (in)  
88.97 x 33.46 x 29.52  
Refrigerator Gross capacity (cu. ft.)  
17  
Freezer Gross capacity (cu ft)  
Net weight (lbs)  
397  
Gross weight (lbs)  
433  
SKU  
RC472701  
2015-12-07  
Page 1

