



Specifications

Copyright © 2014 Dell Inc. All rights reserved. This product is protected by U.S. and international copyright and intellectual property laws. Dell and the Dell logo are trademarks of Dell Inc. in the United States and/or other jurisdictions. All other marks and names mentioned herein may be trademarks of their respective companies.

2014 - 03 Rev. A00

Computer model: Inspiron 5547

Regulatory model: P39F | Type: P39F001

■ NOTE: The images in this document may differ from your computer depending on the configuration you ordered.



Front

Front



Left



Right



Base



Display



Power and battery-status light

Indicates the power state and battery state of the computer.

White light — Power adapter is connected and the battery is being charged.

Amber light — Battery charge is low or critical.

Hard-drive activity light

Turns on when the computer reads from or writes to the hard drive.





Left

Front



Left



Right



Base



Display



Security-cable slot

Connect a security cable to prevent unauthorized movement of your computer.

Power-adapter port

Connect a power adapter to provide power to your computer and charge the battery.

USB 2.0 port

Connect peripherals such as storage devices, printers, and so on. Provides data transfer speeds up to 480 Mbps.

Media-card reader

Reads from and writes to media cards.



Right

Front



Left




Right



Base



Display



Headset port

Connect a headphone, a microphone, or a headphone and microphone combo (headset).

USB 3.0 port

Connect peripherals such as storage devices, printers, and so on. Provides data transfer speeds up to 5 Gbps.

HDMI port

Connect a TV or another HDMI-in enabled device. Provides video and audio output.

Network port

Connect an Ethernet (RJ45) cable from a router or a broadband modem for network or internet access.





Base

Front



Left



Right



Base



Display



Power button

Press to turn on the computer if it is turned off or in Sleep state.

Press to put the computer in Sleep state if it is turned on. Press and hold for 10 seconds to force shut-down the computer.

NOTE: You can customize the power-button behaviour in Power Options. For more information, see Me and My Dell at dell.com/support.

2 Right-click area

Press to right click.

Touchpad

Move your finger on the touchpad to move the mouse pointer. Tap to left-click.

Left-click area

Press to left click.



Display

Front



Left



Right



Base



Display



Left microphone 1

Provides high-quality digital sound input for audio recording, voice calls, and so on.

2 Camera-status light

Turns on when the camera is in use.

Camera

Allows you to video chat, capture photos, and record videos.

Right microphone

Provides high-quality digital sound input for audio recording, voice calls, and so on.



Dimensions and Weight

Height:

Touch 22 mm (0.87 in)

Non touch 21.80 mm (0.86 in)

380.40 mm (14.98 in) Width

259 mm (10.20 in) Depth

Weight:

Touch 2.38 kg (5.25 lb)

Non Touch 2.18 kg (4.81 lb)

NOTE: The weight of your laptop varies depending on the configuration ordered

and the manufacturing variability.





















Audio



















Power Adapter



System Information

Computer model Inspiron 15 Model 5547

4th generation Intel Core i3 ULV Processor

4th generation Intel Core i5 ULV

4th generation Intel Core i7 ULV

L3 cache 4 MB

Chipset Integrated in processor







Ports and Connectors































Memory

Connector Two SODIMM slots

Dual channel DDR3L Type

Speed 1600 MHz

Configurations supported 4 GB, 6 GB, 8 GB, 12 GB, and 16 GB









Connectors











Audio



Media-Card Reader


















Ports and Connectors

External:	
Network	One RJ45 port
USB	One USB 2.0 portTwo USB 3.0 ports
HDMI	One HDMI port
Audio	One headset port
Internal:	
M.2	One M.2-2230 slot for WLAN, Bluetooth, and wireless display (optional)









Connectors









Media-Card

















Communications

10/100 Mbps Ethernet controller integrated on system board **Ethernet** Wireless • Wi-Fi 802.11 ac/b/g/n

- Bluetooth 4.0
- WiDi (optional)



















Audio



















Video

Controller:

Integrated Intel HD Graphics 4400

Discrete AMD Radeon R7 M265

Memory:

Integrated Shared system memory

Discrete 2 GB DDR3

















o | Au



Media-Card Reader



Keyboard













Audio

Controller Realtek ALC3234CG with Waves MaxxAudio

Speakers Two

Speaker output:

2 watt Average Peak 2.5 watt

Microphone Digital array-microphones

Volume controls Media-control shortcut keys



















Audio





















Storage

Interface SATA 6 Gbps

Hard drive One 2.5-inch drive (supports Intel Smart Response Technology)



































Media-Card Reader

One 5-in-1 slot Type Cards supported • SD card • SD 3.0 card • SD High-Capacity (SDHC) card Memory Stick









• Memory Stick PRO



























Display

15.6-inch HD Type

15.6-inch HD touchscreen

15.6-inch full-HD touchscreen

Refresh rate 60 Hz

Operating angle 0 degrees (closed) to 135 degrees

Controls Brightness can be controlled using shortcut keys.

	HD	HD Touch	Full-HD Touch
Resolution (maximum)	1366 x 768	1366 x 768	1920 x 1080
Pixel pitch	0.252 mm	0.252 mm	0.17925 mm
Discounting			

Dimensions

Height 224.30 mm (8.83 in) 225.06	5 mm (8.86 in) 225.06 mm (8.86 in)
Width 344.20 mm (13.55 in) 344.23	mm (13.55 in) 344.16 mm (13.55 in)
Diagonal 360 mm (14.17 in) 366.63	mm (14.43 in) 366.63 mm (14.43 in)











Memory



Ports and Connectors



Communications



Video



Audio



Storage







Keyboard







Touchpad









Keyboard

Type

Standard keyboard

• Backlit keyboard (optional)

Shortcut keys

Some keys on your keyboard have two symbols on them. These keys can be used to type alternate characters or to perform secondary functions. To type the alternate character, press Shift and the desired key. To perform secondary functions, press Fn and the desired key.

NOTE: You can define the primary behavior of the shortcut keys by changing **Function Key Behavior** in System Setup.



Media-Card















Connectors



















Camera

Resolution:

Still image 0.92 megapixels

1280 x 720 (HD) at 30 fps Video

Diagonal viewing angle 74 degrees















Video



Audio



Storage







Display Keyboard

















Touchpad

Resolution:

Horizontal 1260 dpi 1207 dpi Vertical

Dimensions:

Width 105 mm (4.13 in)

Height 80 mm (3.15 in)







Memory



Ports and Connectors































Battery

• 3-cell "smart" lithium ion (43.50 WHr) Type

• 4-cell "smart" lithium ion (58 WHr)

3 cell

	2 0011	
Dimensions:		
Width	208.25 mm (8.20 in)	208.25 mm (8.20 in)
Depth	124.70 mm (4.91 in)	124.70 mm (4.91 in)
Height	7.80 mm (0.31 in)	7.80 mm (0.31 in)
Weight (maximum)	0.28 kg (0.62 lb)	0.35 kg (0.77 lb)
Voltage	11.10 VDC	7.40 VDC
Life span (approximate)	300 discharge/charge cycles	

Temperature range:

Operating 0°C to 35°C (32°F to 95°F)

-40°C to 65°C (-40°F to 149°F) Storage

Coin-cell battery CR-2032

Operating time Varies depending on operating conditions and can significantly reduce under

certain power-intensive conditions.







Ports and Connectors









4 cell

Audio





















Power Adapter

65 W Type

Input voltage 100 VAC-240 VAC

50 Hz-60 Hz Input frequency

1.5 A Input current

Output current 3.34 A

19.50 VDC Rated output voltage

Temperature range:

Operating 0°C to 40°C (32°F to 104°F)

Storage -40°C to 70°C (-40°F to 158°F)







Memory













Video





















Computer Environment

Airborne contaminant level	G1 as defined by ISA-S71.04-1985	
	Operating	Storage
Temperature range	0°C to 35°C (32°F to 95°F)	-40°C to 65°C (-40°F to 149°F)
Relative humidity (maximum)	10% to 90% (non-condensing)	0% to 95% (non-condensing)
Vibration (maximum)*	0.66 GRMS	1.30 GRMS
Shock (maximum)	110 G [†]	160 G [‡]
Altitude (maximum)	-15.2 m to 3048 m (-50 ft to 10,000 ft)	-15.2 m to 10,668 m (-50 ft to 35,000 ft)

^{*} Measured using a random vibration spectrum that simulates user environment.

















Video















[†] Measured using a 2 ms half-sine pulse when the hard drive is in use.

[‡] Measured using a 2 ms half-sine pulse when the hard-drive head is in parked position.