DWS 55100 SERIES

8 Place settings Top control screen



Main Features

4 programs 3 wash temperatures Brushless DC[™] motor Condensing drying system 49 dBA wash noise level Program follow-up display Time delay up to 1-24 hrs. Auto tablet detergent function 1/2 load function ExtraRinse function Extra Drying function RapidClean function 3 way euro filtering system smartFIT[™] front adjustable rear feet smartBALANCE™ front adjustable hinge svstem smartPIN[™] joint handle system Interior highloop with air gap Power plug

Interior Design

All stainless steel tank
Three spray arms (lower, upper and ceiling)

Premium Rack Loading System

FlexiRack[™] loaded adjustable upper rack Upper and lower rack handle 4 adjustable mug shelves Sliding cutlery basket smartFold[™] plate supports on lower rack

Color

DW 55100 SS: Stainless steel DW 55100 FBI: Fully Integrated



FEATURES



8 Place Settings

Blomberg dishwashers can perfectly clean dishes upto 8 place settings without leaving any piece of cutlery out.



RapidClean

The dishwasher increases the washing temperature and adjust the water pressure to provide up to 2 times faster cleaning performance.



Auto Tablet

Sensors detects rinse aid and automaticly sets drying cycle duration. This provides the best drying results without any concern.



Brushless DCTM Motor

Variable speed circulation motor allows to use optimum necessary amount of water and energy. Due to magnetic design the motor has no persistent low frequency sound, and creates less vibration.



Digital Display

The electronic display is a quick and easy way to select your programs. Additionally, models with top control panel wih numerical display offer a noise level adjustable "end of cycle audiable signal". Hidden control panel prevents your children from changing programs and playing with your dishwasher.



Double Motion Float System

All Blomberg dishwashers have a double motion float system (DMFS) that provides maximum security against water damage and a bottom tray to prevent flooding.



DWS 55100 SERIES

8 Place settings Top control screen

Control Type		Electronic
Position		Тор
1AIN FEATURES		
oading Capacity (place settings)		8
Tub material		Stainless Steel
nner door material		Stainless Steel
Water Softener		-
OMFS overflow protection		✓
level wash with 3rd spray arm		✓
elay timer up to 1-24 hrs		✓
way euro filter		✓
rying		Condensation
urbidity sensor		~
ilence level, dBA		49 dBA
ProCare		~
uto Tablet function		~
/2 Load function		~
Sanitize function		-
extraRinse function		~
extra Drying		~
RapidClean function		~
SmartPIN™ joint		✓
Interior high loop with airgap		-
Power Plug		~
PROGRAMS		
lumber of programs		5
Pots and pans plus (167°F rinse temp)		~
Regular Wash (142°F-145°F rinse temp)		~
DailyWash	.,	~
QuickWash (131°F rinse temp)		~
linse & Hold		~
DISPLAY		
rogram sequence		✓/ Screen
Rinse aid indicator		Electronic
Rinse aid indicator display		~
Salt indicator display		-
Light Indicator on Floor		-
RACK SYSTEM		
smartFold™ lower rack folding tines		~
Lower rack embossed stainless handle		-
utlery basket		Standard
Jpper rack (inset shelves)		
Jpper rack (inset shelves)		4
, , ,	nes	-
martFold™, upper rack folding ti		-
martFold™, upper rack folding til lexiRack™, adjustable upper rack		Loaded
martFold™, upper rack folding ti FlexiRack™, adjustable upper rack Jylon coated racks		- Loaded
martFold TM , upper rack folding ti rlexiRack TM , adjustable upper rack lylon coated racks IMENSIONS		Loaded
martFold TM , upper rack folding ti FlexiRack TM , adjustable upper rack Jylon coated racks DIMENSIONS	in	- Loaded
martFold™, upper rack folding ti rlexiRack™, adjustable upper rack lylon coated racks DIMENSIONS racked (HxWxD)	in cm	- Loaded
martFold™, upper rack folding tir FlexiRack™, adjustable upper rack Jylon coated racks DIMENSIONS Packed (HxWxD)	in cm (lb/kg)	- Loaded 34 3/8x19 3/16x26 85.9x49.4x66.1 81/37
martFold™, upper rack folding tii FlexiRack™, adjustable upper rack Jylon coated racks DIMENSIONS Packed (HxWxD)	in cm (lb/kg) in	- Loaded 34 3/8x19 3/16x26 85.9x49.4x66.1 81/37 32 1/4x17 3/4x22 2/5
martFold™, upper rack folding ti FlexiRack™, adjustable upper rack Jylon coated racks DIMENSIONS Packed (HxWxD) Packed Weight Jnpacked (HxWxD)	in cm (lb/kg) in cm	- Loaded 34 3/8x19 3/16x26 85.9x49.4x66.1 81/37 32 1/4x17 3/4x22 2/5 81.8x45x57
martFold™, upper rack folding tii ilexiRack™, adjustable upper rack lylon coated racks IJMENSIONS lacked (HxWxD) lacked Weight Inpacked (HxWxD)	in cm (lb/kg) in	- Loaded 34 3/8x19 3/16x26 85.9x49.4x66.1 81/37 32 1/4x17 3/4x22 2/5
martFold™, upper rack folding tii FlexiRack™, adjustable upper rack lylon coated racks DIMENSIONS Packed (HxWxD) Packed Weight Jnpacked (HxWxD) Jnpacked Weight	in cm (lb/kg) in cm	- Loaded 34 3/8x19 3/16x26 85.9x49.4x66.1 81/37 32 1/4x17 3/4x22 2/5 81.8x45x57 75/34
martFold™, upper rack folding til elexiRack™, adjustable upper rack lylon coated racks DMENSIONS Packed (HxWxD) Packed Weight Jnpacked (HxWxD) Jnpacked Weight ENVIRONMENTAL STANDARDS Energy Star qualified	in cm (lb/kg) in cm	- Loaded 34 3/8x19 3/16x26 85.9x49.4x66.1 81/37 32 1/4x17 3/4x22 2/5 81.8x45x57 75/34
martFold™, upper rack folding tii ilexiRack™, adjustable upper rack lylon coated racks iMENSIONS lacked (HxWxD) lacked Weight linpacked (HxWxD) Inpacked Weight Invironmental Standards	in cm (lb/kg) in cm	- Loaded 34 3/8x19 3/16x26 85.9x49.4x66.1 81/37 32 1/4x17 3/4x22 2/5 81.8x45x57 75/34

^{*} Lead-free





