



30" GAS DROP-IN COOKTOP **E30GC64ESS**



### 30" Gas Drop-In Cooktop Specifications

- Product Weight – 50 Lbs.
- Voltage Rating – 120V/60 Hz/15 Amp
- Always consult local and/or national electric and gas codes.
- Access to the underside of cooktop and junction box must be provided for inspection and service.
- Cooktop ships with 3/4" factory regulator.
- Allow 30" minimum clearance between top of cooktop and bottom of unprotected wood or metal overhead cabinetry.
- Allow 24" minimum clearance when bottom of wood or metal overhead cabinet is protected by not less than 1/8" flame-retardant millboard covered with not less than No. 28 MGS sheet steel, 0.015" stainless steel, 0.024" aluminum or 0.020" copper.
- Recommended distance from rear edge of cooktop to nearest vertical combustible surface is 2-1/2" to backsplash or 3-1/8" to rear wall.
- Allow 7-1/2" minimum clearance from edge of cooktop to nearest combustible wall on either side of unit.
- Allow 2-1/2" minimum clearance between bottom of cooktop chassis and all combustible surfaces including upper edge of drawer installed beneath cooktop.
- Beneath cooktop, allow 29" minimum width between cabinet sidewalls.
- A fixed shelf should not be installed beneath cooktop.
- Overhead cabinetry should not exceed a 13" maximum depth.
- To reduce risk of fire when using overhead cabinetry, install range hood that projects horizontally a recommended minimum of 5" beyond bottom of cabinets.

**Note:** Refer to Product Installation Guide for detailed instructions on the web at [www.electroluxusa.com](http://www.electroluxusa.com).

### 4 Sealed Burner Configuration

Four high output burners, one 14,000 BTU, one 12,500 BTU and two 8,500 BTU make this cooktop as versatile as it is precise. The burners are sealed for easy cleanup.

### Flush Surface

The slightly recessed stainless steel surface contains spills and aids in cleaning.

### Interlocking Grates

Designed for cooking multiple dishes at varying temperatures on a single cooktop. Interlocking grates spread weight over a broad area providing a stable cooking surface.

### 30" GAS DROP-IN COOKTOP

Configuration	4 Sealed Burners
---------------	------------------

### FEATURES

Formed Stainless Steel Platform	Yes
Large Professional Skirted Knobs with Bezel	4
Sealed Burner – 14,000 BTU	1
Sealed Burner – 12,500 BTU	1
Sealed Burner – 8,500 BTU	2
Simmer Burner – 850 BTU	Yes
Linear Flow Burner Valves	4
Electronic Ignition with Re-Ignition	Yes
Interlocking Grates	2

### SPECIFICATIONS

Gas Inlet Location	Right Rear
LP Conversion Kit	Included
Voltage Rating	120V / 15 Amp
Electrical Cable	Included
Shipping Weight	53 Lbs.
UPC (0-12505-)	53948-0

NOTE: Always consult local and/or national electric codes. Refer to Product Installation Guide for detailed installation instructions on the web at [www.electroluxusa.com](http://www.electroluxusa.com).

