



SOAP / LOTION DISPENSER INSTALLATION INSTRUCTIONS

ITEM SL5060 - TRADITIONAL
ITEM SL5065 - CONTEMPORARY

*** TOOLS NEEDED**
Adjustable Wrench

SPECIFICATIONS
• MAX COUNTER THICKNESS 2-3/8"
• INSTALL HOLE SIZE 1-3/8"
• LARGE CAPACITY CLEAR BOTTLE
• SOLID BRASS CONSTRUCTION

STEP ONE	STEP TWO	STEP THREE	STEP FOUR
<p>Remove top (A) from dispenser body (B). Remove spacer (C) and nut (D) from threaded shroud.</p>	<p>Select desired position and drill 1-3/8" hole in counter or sink. Fit dispenser body through hole.</p>	<p>Slide spacer (C) to underside of sink or counter. Thread nut (D) and tighten securely.</p>	<p>Thread bottle (E) into bottom of dispenser shroud. Add soap or lotion from top of dispenser into bottle.</p>

STEP FIVE	STEP SIX	STEP SEVEN
<p>Slide clear tubing (F) into tube fitting (G) at bottom of spout.</p>	<p>Insert open end of clear tubing down through dispenser and into bottle.</p>	<p>Insert top. Pump spout a few times to begin flow of soap or lotion.</p>

www.bti-aquasolutions.com

7022 South Revere Parkway • Suite 240 • Centennial, CO 80112 • 720.322.0800 (o) 720.322.0801 (f)



BTI AQUA-SOLUTIONS SOAP/LOTION DISPENSER CARE & WARRANTY

Congratulations – you’ve just added a quality BTI Aqua-Solutions product to your home.
With proper care, it will remain beautiful for years to come.
Please review this information in its entirety and follow the instructions carefully.

CARE INSTRUCTIONS FOR CHROME, BRUSHED NICKEL AND POLISHED NICKEL FINISHES

IMPORTANT: It is the customer’s responsibility to check for any material finish defects BEFORE installation.

The best general maintenance is regular cleaning. Even though these finishes are considered durable, you CAN NEVER use any abrasive type cleaners, sponges, cloths or pads to clean the fixture. Always try to keep the finish clean and dry. Trapped moisture on the surface of the finish can lead to staining. Astringent cleaners, chlorine, bleach, along with acidic based organic cleansers are potentially harmful to these finishes.

RECOMMENDED MAINTENANCE: Do not allow water spots to dry on the fixture. Keep the surface dry and clean after use. All products should be cleaned with a damp, clean, soft cloth and mild, nonabrasive soap to remove surface spots. Be gentle in your cleaning method.

FINISH & FUNCTIONAL WARRANTY

Finish Warranty		
Finishes Warrantied:	Chrome (CH)	Lifetime
	Brushed Nickel (BN)	7-years
	Polished Nickel (PN)	7-years
Functional Warranty		5-years

To file a warranty claim for a functional or finish defect, a dated receipt of purchase of the product from an Authorized BTI Dealer must accompany the warranty request. To submit a warranty claim, contact: warrantyservices@btiaquasolutions.com

Improper installation, the failure to perform proper maintenance, or uses for which the products were not designed are not warranted.

The warranty will be void if the finish has been improperly cared for due to lack of cleaning or cleaning with improper cleaning materials which result in damage. BTI Aqua-Solutions has no liability for indirect or consequential damages to its products. The finish warranty is for normal wear and tear of the finished surface.

BTI Aqua-Solutions will repair or replace, at its option, any product that BTI has determined to have a manufacturing defect. BTI Aqua-Solutions is not responsible for any installation or labor charges and will not pay for any repair cost performed on its products without prior written consent by a BTI Aqua-Solutions authorized representative.

Eco-Friendly, Next-Generation Products of Tomorrow...Today!